NO. OF COPIES RECE	VED	Form C-103	
DISTRIBUTION		Supersedes Old C-102 and C-103	
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65	
FILE			
U.S.G.S.	San 21 12 55 777 35	5a. Indicate Type of Lease	
LAND OFFICE		State X Fee	
		5. State Oil & Gas Lease No.	
OPERATOR		State - R-1258-1	
	SUNDRY NOTICES AND REPORTS ON WELLS		
(DO NOT USE	SUNDRY NOTICES AND REPORTS ON WELLS THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	7. Unit Agreement Name	
I.	GAS OTHER-	NONE	
2. Name of Operator	WELL L OTHER-	8. Farm or Lease Name	
Z, Hans of Operator	TEXACO Inc.	State of N. M. "AE"	
3. Address of Operato		9. Well No.	
	P. O. Box 728 - Hobbs, New Mexico	22	
4. Location of Well		10. Field and Pool, or Wildcat	
	D 985 PEET FROM THE West LINE AND 330 PEET FROM	Vacuum	
UNIT LETTER			
North	LINE, SECTION NORth / TOWNSHIP T-18-5 RANGE 34-E NMPM.		
THE			
milling	15. Elevation (Show whether DF, RT, GR, etc.)	12. County	
	3990' (GR)	Lea	
16.	Check Appropriate Box To Indicate Nature of Notice, Report or Oth	er Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
	NOTICE OF INTERVIOUS VOI		
PERFORM REMEDIAL W	ORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDO	CONVENCE DRIVE INC. ODN.	PLUG AND ABANDONMENT	
PULL OR ALTER CASIN	CARLING TEST AND CEMENT ION X		
FUEL ON AETER GASTA	OTHER		
OTHER			
VIII.			
17. Describe Propose	d or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any proposed	
work) SEE RULE	. 11081,		
	Total Depth - 1600		
Spudded 9 7/8" 0. D. Hole at 2:15 P. M. September 17, 1965			
Space of the note			
	Ran 1588' of 7 5/8" O. D. Casing, 15.28 LB, Spiral Weld, N	EW. and cemented	
at 1600' with 500 Sx. Trinity Lite Wate, plus 200 Sx. Class "C" with 1% CC.			
Plug at 1570'. Cement Circulated.			
•			
	Temperature of mixing slurry - 86°, 12 Hour Strength - 1000 P. S. I.		
Temperature of mixing slurry - 86°, 12 Hour Strength - 1000 P. S. I. Bottom Hole Temperature - 82°, Job complete 8:15 P. M. September 19, 1965.			
Tested 7 5/8" 0. D. Casing for 30 minutes with 600 P. S. I. from 7:00 A. M.			
to 7:30 A. M. Tested O. K. Drilled cement plug and re-tested for 30			
minutes with 600 P. S. I. from 9:00 A. M. to 9:30 A. M. September 20, 1905.			
	Tested O. K. Job complete 9:30 A. M. September 20, 1965.		

Superintendent

September 21, 1965

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CONDITIONS OF APPROVAL, IF ANY