

OIL CONSERVATION COMMISSION

P. O. BOX 2088

SANTA FE, NEW MEXICO

May 25, 1965

C
O
P
Y

Texaco Inc.
Drawer 728
Hobbs, New Mexico

Attention: Mr. H. D. Raymond

Gentlemen:

Reference is made to your letter dated May 3, 1965, wherein you request authority to complete your State of New Mexico "R" (NCT-2) Well No. 5 located in Unit B, Section 2, Township 18 South, Range 34 East, Lea County, New Mexico, as a tubingless completion in the Vacuum San Andres Pool.

It is our understanding that 2-7/8 inch casing will be set at approximately 6250 feet and perforated from approximately 5926 feet to 5946 feet in the Lower San Andres formation. Sufficient cement will be used to come back to the base of the salt estimated to be at 2670 feet.

Texaco Inc. is hereby authorized to complete the subject well in the aforesaid manner.

Very truly yours,

A. L. PORTER, Jr.,
Secretary-Director

ALP/DSN/og

cc: Oil Conservation Commission - Hobbs
Oil & Gas Engineering Committee - Hobbs

COUNTY	LEA		FIELD	Vacuum		STATE	N.M.	
OPR	TEXACO INC.					MAP		
5 State of New Mexico "R" (NCT-2)								
Sec. 2, T-18-S, R-34-E						CO-ORD		
330' fr N Line & 1650' fr E Line of Sec.								
Spud 3-17-65			CLASS	E [REDACTED]				
Cmp 5-13-65			FORMATION	DATUM	FORMATION	DATUM		
CSG & SX - TUBING			LOG:					
10 3/4"	1550'	800	Glor 6010					
2 7/8"	6248'	1000						
LOGS EL GR RA IND HC A			TD 6250', PBD 5984'					

IP San Andres Perfs 5926-46' Pmpd 7 BOPD + 15 BW. Pot. Based on 24 hr test, gravity 38., GOR TSTM.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	6250'	TYPE
DATE			

F. R. 1-7-65.
PD 6250' - Glorieta.
3-22-65 Drlg. 3340'.
3-29-65 Drlg. 5304' 1m.
4-5-65 TD 6250', prep to run csg.
4-12-65 TD 6250', PBD 6243', prep to perf.
Perf. @ 6052', 6059', 6061' W/1 SPI.
Ac. 500 gals.
Swbd. 33 BLW/4 hrs.
Re-Ac. 500 gals. 6052-61'.
Swbd. 48 BLW/8 hrs.
Re-Ac. 2400 gals. 6052-61'.
Swbd. 61 BLW/13 hrs.
Swbd. dry.
4-19-65 TD 6250', PB 6243', swbg.
Perf. @ 6100', 6102', 6104', 6106' W/1 SPI.
Ac. 2400 gals. 6052-6106'.
Swbd. 22 BLW/12 hrs.

- cont'd -

4-19-65 Continued
[REDACTED] Perf @ 6178', 6180', 6182' W/2 SPI
Ac. 2000 gals. 6178-82'.
Swbd 83 BLW + 250 BFW in 34 hrs.
4-26-65 TD 6250', PBD 5984', S1.
Set BP @ 6000'
Perf @ 5926', 5928', 5934', 5941',
5946' W/1 SPI
Ac. 500 gals.
Swbd 41 BLW in 3½ hrs.
Re-Ac. 1500 gals. 5926-46'
Swbd 68 BLW in 4 hrs.
5-3-65 TD 6250', PBD 5984', swbg.
Re-Ac. 6000 gals. 5926-46'.
Swbd 36 BNO + 179 BLW + 35 BFW in 16 hrs.

5-10-65 TD 6250', PBD 5984', cstg on pump.
Pmpd 12 BO + 33 BW in 18 hrs.
5-17-65 TD 6250', PBD 5984', COMPLETED.