

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANITARY	
FILE	
U.S.G.S.	
LAND	
OPER	

NEW MEXICO OIL CONSERVATION COMMISSION

Form O-103
Revised 8-1971
O-103 and O-104
Effective 1-1-65

1. Lease Type or Name	Fee <input type="checkbox"/>
2. Lease No. or Lease No.	
B-1306-1	
3. Well Name	
New Mexico 'R' State	
4. Well No.	
11	
5. Field, or Wildcat	
Vacuum Glorieta	
6. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG WELL TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - (FORM O-101) FOR SUCH PROPOSALS.)

1. Type of Notice	2. Name of Operator
<input checked="" type="checkbox"/> OIL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	TEXACO Inc.
3. Address of Operator	
P.O. Box 728, Hobbs, New Mexico 88240	
4. Location of Well	
UNIT LETTER <u>H</u> <u>990</u> FEET FROM THE <u>East</u> LINE AND <u>1650</u> FEET FROM THE <u>North</u> LINE, SECTION <u>6</u> TOWNSHIP <u>18S</u> RANGE <u>35E</u> N.M.P.M.	

5. Elevation (Show whether DE, RT, GR, etc.)	
3980 DE	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPER. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <u>Squeeze to shut off Yates water</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent measurements, for work) SEE RULE 1103.

1. Pulled rods and pump.
2. Ran temperature survey and located water entry @ 2450'.
3. Ran RBP in 2 7/8" casing and set @ 5000', dumped 1 sx sand on plug.
4. Perforate 2 7/8" casing w/4 holes @ 2514'. Set cement retainer @ 2460' and squeezed w/600 sx Class 'C' cement w/18% salt and 2% CaCl.
5. Drilled out retainer and cement. Squeezed perforations w/50 sx Thixomix followed by 50 sx Class 'C' cement.
6. Drilled out cement, Squeezed w/250 sx Class 'C' cement w/10 # sand per sack, 2% CaCl followed w/250 sx Class cement.
7. Drilled out cement. Ran 1 1/4" IJ tubing between 10 3/4" casing and 2 7/8" casing to 1550'. Spotted 300 sx Class 'H' cement w/2% CaCl from 1550-830. Pulled 1 1/4" tubing.
8. Squeezed perforations at 2514' w/ 250 sx Class 'H' w/ 2% CaCl.
9. Squeezed perfs w/1000 Gal Howco injectrol and 50 sx Class 'H' Cement w/ 2% CaCl @ 2514'.
10. Drill out Cement, tested to 1600 #. Tested OK.
11. Pulled RPB, Ran rods, tubing and pump. Test and return to production.

18. I hereby certify that the information above is true and complete to the best of my knowledge.	
SIGNED <u>[Signature]</u>	TITLE <u>Asst. Dist. Supt.</u>
Orig. Signed By <u>John Runyan</u> Geologist	
APPROVED BY _____	TITLE _____
CONDITIONS OF APPROVAL, IF ANY:	

3-27-75

APR 2 1975

RECEIVED

APR 4 1975

U.S. CONSERVATION COMM.
WASHINGTON, D.C.