

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
State - B-1306-1

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	NONE
3. Address of Operator	8. Farm or Lease Name
TEXACO Inc.	St. N.M. "R" NCT-1
4. Location of Well	9. Well No.
UNIT LETTER <u>H</u> <u>990</u> FEET FROM THE <u>East</u> LINE AND <u>1650</u> FEET FROM	10. Field and Pool, or Wildcat
THE <u>North</u> LINE, SECTION <u>6</u> TOWNSHIP <u>18-S</u> RANGE <u>35-E</u> NMPM.	Vacuum Glorieta
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3973' (GR)	Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total Depth - 1497'
Spudded 13 3/4" Hole at 6:00 A. M. April 23, 1965

Ran 1487' of 10 3/4" O. D. Casing, 28.52 LB, NEW, Spiral Weld, and cemented at 1497' with 600 Sx. Class "A" 10% gel, plus 200 Sx. Class "C" neat with 2% CACL. Plug at 1467'. Cement Circulated. Job complete 1:15 A. M. April 27, 1965.

Temperature of mixing slurry - 86 degrees, Strength 12 Hours 1600 P. S. I.
Bottom Hole temperature - 77 degrees.

Tested 10 3/4" O. D. Casing for 30 minutes with 600 P. S. I. from 9:30 A. M. to 10:00 A. M. April 27, 1965. Tested O. K. Drilled cement plug and re-tested for 30 minutes with 600 P. S. I. from 10:30 A. M. to 11:00 A. M. April 27, 1965. Tested O. K. Job complete 11:00 A. M. April 27, 1965.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. D. Raymond TITLE Assistant District Superintendent DATE April 28, 1965

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: