

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRI-
(Other instructio
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

L.C. 65710-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Lusk Deep Unit

8. FARM OR LEASE NAME

Lusk Deep

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Lusk *Strawn*

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

20-19S-32E

12. COUNTY OR PARISH

13. STATE

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR
El Paso Products

3. ADDRESS OF OPERATOR
c/o Hobbs Pipe & Supply Co., Box 2010, Hobbs, N.M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

UK

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

1. Spotted a 25 sx cement plug to cover existing perforations, 11,430'-11,470'.
2. Spotted a 25 sx cement plug at stub of 4 1/2" casing at 5,500'.
3. Spotted a 35 sx cement plug at base of 9-5/8" casing (4,226').
4. Spotted a 25 sx cement plug at 2,400' - 2,500'.
5. Spotted a 25 sx cement plug at 700' - 800'.
6. Spotted a 10 sx cement plug at top.
7. Hole was loaded with mud-laden fluids and a 4" regulation marker was erected.
8. Well was plugged and abandoned on 10/9/71.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AGENT

DATE

10/20/71

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED