

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
El Paso Products Company

3. ADDRESS OF OPERATOR
c/o Hobbs Pipe & Supply Company, Box 2010, Hobbs, N.M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

5. LEASE DESIGNATION AND SERIAL NO.
LC 065710-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Lusk Deep Unit

8. FARM OR LEASE NAME
Lusk Deep Unit

9. WELL NO.
4

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
20-19S-32E

12. COUNTY OR PARISH
Lea

13. STATE
N. M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
UK

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work, if well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Proposed Plugging Procedures:

1. Spot a 25 sx cement plug to cover existing perforations.
2. Spot a 25 sx cement plug at stub of 4 1/2" casing.
3. Spot a 35 sx cement plug at base of 9-5/8" casing - (4226')
4. Spot a 25 sx cement plug at 2400' - 2500'.
5. Spot a 25 sx cement plug at 700' - 800'.
6. Spot a 10 sx cement plug at top.
7. Hole will be loaded with mud-laden fluids and a 4" regular marker erected.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Agent

DATE 9/16/71

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE APPROVED DATE

SEP 17 1971

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

TO: DIRECTOR, FBI
FROM: SAC, NEW YORK
SUBJECT: [Illegible]

RECEIVED

SEP 21 1971

OIL CONSERVATION COMMISSION
WASHINGTON, D. C.