

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

HOBBS OFFICE O. C. C.

Nov 18 10 41 AM '66

Form C-101
Revised 1-1-65

5A. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
5. State Oil & Gas Lease No. E-1582
7. Unit Agreement Name
8. Farm or Lease Name Sinclair Vacuum SWD
9. Well No. 1
10. Field and Pool, or Wildcat Undesignated
12. County Lea
19. Proposed Depth 6600'
19A. Formation see below
20. Rotary or C.T.
21. Elevations (Show whether DF, RT, etc.) 3915 GR
21A. Kind & Status Plug. Bond In effect
21B. Drilling Contractor
22. Approx. Date Work will start Upon approval

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK	
1a. Type of Work Re-enter plugged & abandoned hole	
b. Type of Well DRILL <input type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> SINGLE ZONE <input type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>	
2. Name of Operator Sinclair Oil & Gas Company	
3. Address of Operator P.O. Box 1920, Hobbs, New Mexico	
4. Location of Well UNIT LETTER 0 LOCATED 735 FEET FROM THE South LINE AND 2055 FEET FROM THE East LINE OF SEC. 16 TWP. 18S RGE. 35E NMPM	
21. Elevations (Show whether DF, RT, etc.) 3915 GR	21A. Kind & Status Plug. Bond In effect
21B. Drilling Contractor	
22. Approx. Date Work will start Upon approval	

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
	13-3/8"OD	H-40 48#	406'	410	CIRCULATED
	9-5/8"OD	32# & 36#	3990'	1750	CIRCULATED

NOTE: Above casing is now in hole, there will be no further casing set.

THIS WELL WAS DRILLED AS Sinclair Oil & Gas Company's State Lea 403 Well No. 7 and plugged and abandoned as dry hole on completion in December, 1965.

By Order No. SWD-62 approved November 5, 1966, New Mexico Oil Conservation Commission approved re-entry of this plugged hole for use as salt water disposal well.

Present cement plugs (10 sks in top of 9-5/8"csg; 25 sks f/3950-4000; and 25 sks f/5450-5500) will be cleaned out and a cement plug will be set from 6600' to 6730'.

Will dispose of water into Yates-Queen; San Andres-Delaware formation as approved by SWD-62.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE, GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed W. Singleton Title Engineer Date Nov. 18, 1966

(This space for State Use)
APPROVED BY Joe Gomez TITLE Director DATE Nov. 18, 1966
CONDITIONS OF APPROVAL, IF ANY: