NO. OF COPIES RECEIVED	7	_
DISTRIBUTION	Hanna	Form C-103 Supersedes Old
SANTA FE	HORES OFFICE OF C. C.	C-102 and C-103
FILE	Jan C C	Effective 1-1-65
U.S.G.S.	JAN 6 3 00 PM 66	5a. Indicate Type of Lease
LAND OFFICE	]	State X Fee
CPERATOR		5. State Oil & Gas Lease No.
· · · · · · · · · · · · · · · · · · ·		E-1582
(DO NOT USE THIS FORM FOR PR USE "APPLICA"	RY NOTICES AND REPORTS ON WELLS  OPOSALS TO DRILL OR TO DEEPEN OF PLUG BACK TO A DIFFERENT RESERVOIR. TION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
OIL GAS WELL	OTHER•	7. Unit Agreement Name
2. Name of Operator Sinclair Oil & Gas Company		8, Farm or Lease Name State Lea 403
P.O. Box 1920, Hobbs, New Mexico		9. Well No.
4. Location of Well  UNIT LETTER 0 7	35 FEET FROM THE South LINE AND 2055 FEET FROM	10. Field and Pool, or Wildcat Undesignated
		CHO ESTENS LEG
THE LINE, SECTI	RANGE NMPM	
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea
Check	Appropriate Box To Indicate Nature of Notice, Report or Ot	
1101102 01 11	SUBSEQUEN'	T REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON X REMEDIAL WORK	
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	ALTERING CASING
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	PLUG AND ABANDONMENT
	OTHER	
OTHER		
17. Describe Proposed or Completed Or work) SEE RULE 1103.	perations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any proposed
Confirming verbal	approval to plug well received from Eri	
D.N. Williams.		- 11601001100
PROPOSE TO PLUG AN	ND ABANDON DRY HOLE AS FOLLOWS; with hol	a full of honor mud
125 sack cement p	lug 10350-10750	e lull of heavy mud.
125 sack cement p	lug 9450-9650	
25 sack cement plu	ag 9310-9360 (top of Wolfcamp) ag 6730-6782 (top of Bone Springs)	
25 sack cement plu	lg 6730-6782 (top of Bone Springs)	
25 sack cement pit	ag 5450-5500 (base of San Andres)	
10 sack cement plu	ag 3950-4000 (base of 9-5/8" casing) ag in top of 9-5/8 casing & cellar.	
Set Regulation Man	ker and Clean and Level Location.	
Drilling Record:	13-3/8" Casing set at 406' and cement c	irculated to surface.
	9-5/8" Casing set at 3990 and cement c	irculated to surface,
	total depth drilled: 10,946	
8. I hereby certify that the information	above is true and complete to the best of my knowledge and belief.	
- In mornation	tue and complete to the best of my knowledge and belief.	
review	Superintendent	1-4-66
IUNE	ALLE DAPATITION OF C	. DATE