

1-3-66 Continued
Perf @ 4698', 4701', 4703' W/1 SPI
Ac (4698-4703') 500 gals.
Swbd dry.
1-10-66 TD 4766', PBD 4666', swbg.
Ac (4698-4703') 1000 gals.
Swbd dry
Frac (4698-4703') 5000 gals gelled wtr
+ 5000# sd.
Swbd 155 BLW + 55 BFW/24 hrs.
Squeezed perfs 4698-4703'.
Perf @ 4677', 4680', 4684' W/1 SPI
Ac (4677-84') 250 gals.
Frac (4677-84') 5000 gals gelled wtr +
5000# sd.
Swbd 160 BLW + 40 BFW.

Squeezed perfs 4677-84' W/75 sx.
Perf @ 4611', 4618', 4620', 4627',
4631' W/1 SPI
Ac (4611-31') 500 gals.
Frac (4611-31') 5000 gals gelled wtr +
5000# sd.
Swbd 160 BLW/12 hrs.
1-17-66 TD 4766', PBD 4468', SI.
Swbd 90 BLW + 55 BFW/24 hrs (4611-31')
Squeezed perfs 4611-31'.
Perf @ 4512', 4516', 4531', 4534' W/1 SPI
Ac (4512-34') 500 gals (MA)
Swbd down.
Frac (4512-34') 10,000 gals gelled wtr +
10,000# sd. IR 10 BPM @ 3600#.

1-17-66 Continued
Swbd 86 BLW/12 hrs (4512-34')
Swbd dry
Squeezed perfs 4512-34'.
Perf @ 4337', 4339', 4342' W/3 SPI
Ac (4337-42') 500 gals.
Frac (4337-42') 10,000 gals gelled wtr
+ 10,000# sd; IR 14 BPM @ 4500#
Swbd 132 BLW/12 hrs
Swbd dry
1-24-66 TD 4766', PBD 4468', PLUGGED & ABANDONED.
LOG TOPS: Yates 2740', Queen 3848',
Grawburg 4261', Premier 4606', San
Andres 4751'.