

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instruction
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 067982 2

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Shell "A" Federal

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Lusk (Seven Rivers)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

3, T19S, R32E

12. COUNTY OR PARISH 13. STATE

Lea

N Mex

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐	2. NAME OF OPERATOR Cactus Drilling Company	3. ADDRESS OF OPERATOR P O Drawer 2066, Hobbs, New Mexico	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit N, 990' FS, 1980' FW Lines, Sec. 3.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3667.7 OL, 3678 DF
---	--	--	---	--

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to depth of 3859'. Drill stem tested Zone 3576 to 3635 w/recovery of 725' drilling mud and no oil or gas show. Cored interval 3825' to 3859' with no show of oil or gas. Ran GR/D/C log and zone considered non productive. Mr. A. R. Brown, USGS, verbally granted authority to proceed with plugging well in the following manner:

30 sx cement plug 3859-3769; 30 sx cement plug 2815-2725;
30 sx cement plug 1350-1260; 30 sx cement plug 360-270;
10 sx cement plug at surface. All intervals between cement plugs to be filled w/mud.

18. I hereby certify that the foregoing is true and correct

SIGNED J. L. Gordon TITLE Vice PresidentDATE 17 February 66

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

APPROVED

FEB 21 1966

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

NOBBS OFFICE O.C.C.
MAR 1 1 1964