

SINCLAIR OIL & GAS COMPANY
P. O. Box 1920, Hobbs, New Mexico

HOOPER & CO. O.C.C.

JUN 3 11 22 AM '66

R. D. Lee Well No. 1, Unit Ltr B, 2310' from the East line and 330' from
the North line, S₁c. 2-T18S-R35E NMPM, Lea Co., New Mex.

Item No. 17 (Cont'd)

- 5-21-66 Squeezed Bone Springs Open Hole 9010-9015' w/50 sacks Incor Cement
plus .8 of 1% Halad 9 Max. Press. 5500#, reversed out 14 sacks.
WOC 24 hrs.
- 5-22-66 Pressure tested casing to 1000# for 30 mins., tested o.k.
Jet perforated Bone Springs 8967-8992' w/25-1/2" holes.
- 5-23-66 M.A. washed Bone Springs perfs. 8967-8992' w/250 gals. Max. Press.
4800#, no break @ 1/2 BPM., Inst. SIP 4600#, 15 mins. SIP 4400#.
12 hr. SIP 0#. Ran swab no measureable recovery.
- 5-25-66 Filled hole w/heavy mud. Spotted 25 sacks cement 8996-8800' across
to perforations. Cut and pulled 2590' of 4-1/2"OD casing. Spot 10
- 5-27-66 sacks cement in top of 13-3/8"OD casing and cellar. Installed
Regulation dry hole marker, cleaned and levelled location. Plug and
Abandoned effective 5-27-66.