

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

HOBBS OFFICE C. C. C.
 NEW MEXICO OIL CONSERVATION COMMISSION
 MAY 31 2 40 PM '66

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name
2. Name of Operator Sinclair Oil & Gas Company		8. Farm or Lease Name R.D. Lee
3. Address of Operator P.O. Box 1920, Hobbs, New Mexico		9. Well No. 1
4. Location of Well UNIT LETTER <u>B</u> <u>2310</u> FEET FROM THE <u>East</u> LINE AND <u>330</u> FEET FROM THE <u>North</u> LINE, SECTION <u>2</u> TOWNSHIP <u>18S</u> RANGE <u>35E</u> NMPM.		10. Field and Pool, or Wildcat Buckeye Abo
15. Elevation (Show whether DF, RT, GR, etc.)		12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
 TEMPORARILY ABANDON ☐
 PULL OR ALTER CASING ☐
 OTHER ☐

PLUG AND ABANDON ☒
 CHANGE PLANS ☐
 OTHER ☐

REMEDIAL WORK ☐
 COMMENCE DRILLING OPNS. ☐
 CASING TEST AND CEMENT JOBS ☐
 OTHER ☐

ALTERING CASING ☐
 PLUG AND ABANDONMENT ☐
 OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total depth drilled: 9015'
 13-3/8" csg set at 373' & cement circulated to surface.
 8-5/8" csg set at 3600' and cemented back to 300' fr surface.
 4-1/2" csg set at 9010' and cemented back to 2660' fr surface.
 4-1/2" casing perforated 8697'-8992'

Dry Hole - propose to plug and abandon as follows:
 Cover perms 8697-8992 w/25 sks cement plug from 8800-8996.
 Cut & pull 4-1/2" csg from 2590'
 Set 10 sk cement plug in top of 13-3/8" csg w/regulation dry hole marker.
 (Will leave hole full of heavy mud).

(confirming verbal from Joe Ramey to Doyle Williams 5-25-66)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Superintendent DATE 5-25-66

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: