

1-28-81 Dresser Atlas perforated with 4" Jumbo Jet Gun two shots every other foot as follows:

9010-9020')
9026-9050') - Total of 66 holes
9054-9080')

TIH with Baker Model "R" Double Grip Pkr. and set at 8969'. Swabbed.

1-29-81 Howco acidized down 2 7/8" tbg. with 1850 gals. MCA (spotted 100 gals. across perfs.). AIR of 2.5 BPM at 2200 psi. Used 90 ball sealers. ISIP 1600 $\frac{\#}{\text{g}}$ and 15 min. SIP 1300 $\frac{\#}{\text{g}}$.

1-30-81 Swabbed.

1-31-81 Swabbed well dry. Halliburton acidized with 4000 gals. Mod 202 acid and three 200 $\frac{\#}{\text{g}}$ rock salt blocks using 36 ball sealers and 1500 SCF N₂/bbl. at a combined AIR of 5 BPM. Maximum pressure 2830 $\frac{\#}{\text{g}}$.

2-1 to 2-3-81 Swabbed.

2-4-81 Released pkr. TOH with tbg. and pkr. WIH with 15' orange peel mud anchor, 2 jts. tbg., 2 7/8" x 5 1/2" tbg. anchor and rest of tbg.

2-5-81 Ran 1 1/2" Bore Pump and rods. ,

2-6-81 Installed pumping equipment. Previous Status: P&A. Swab Test: 5-50% oil.

2-9-81 Built pad for tank battery.

Waiting on tanks and electrification.