

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
verse side)

TE*

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

L.C. 0997

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal MA

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Indesignated

11. SEC., T., E., M., OR BLK. AND

Sec. 27, T-18S, R-33E
N.M.P.M.

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

1. OIL WELL ☒ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

AZTEC OIL & GAS COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 837, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1980 FNL and 1980 FEL, Sec. 27, T-18S, R-33E
Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3806 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Surface casing

(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log-Form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Surface casing was set in the following manner:

- Spudded at 2:00 p.m. January 23, 1967. Drilled 17 1/2" hole to 395'. Ran 12 joints of 13-3/8", 48#, H-40 casing to 393'. Cemented with 300 sxs. Class 'A' regular cement with 4% gel and 2% calcium chloride. Pumped plug to 353' at 5:00 a.m. 1/24/67. Cement circulated.
- After 18 hours tested casing to 800 psi before and after drilling out cement for 30 minutes. O. K.

18. I hereby certify that the foregoing is true and correct

SIGNED

LESTER L DUKE

TITLE

District Superintendent

DATE

January 30, 1967

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.