

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 062514-PA

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FEDERAL "PA"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

SOUTH CORBIN WOLFCAMP

11. SEC., T., R., M., OR BLK. AND

SURVEY OR AREA
Section 25-188-33E
NM PM

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

1.

OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

AZTEC OIL & GAS COMPANY

3. ADDRESS OF OPERATOR

P. O. BOX 837, HOBBS, NEW MEXICO 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980 FS & EL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3826.7 DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was plugged and abandoned 10-24-70. Cement plugs were set in the following manner:

1. 25 sx cement plug at 8350' on top of 5 1/2" casing stub.
2. 25 sx cement plug set at 5500'-5600'.
3. 25 sx cement plug set at 4800' at shoe of 8-5/8" casing.
4. 35 sx cement plug set at 2800'-2900'.
5. 35 sx cement plug set at 850' top of 8-5/8" stub.
6. 35 sx cement plug set at 342' shoe of 13-3/8" casing.
7. 10 sx cement plug set at Surface w/Dry Hole Marker.

All plugs were spotted w/10# mud.

18. I hereby certify that the foregoing is true and correct


ORIGINAL SIGNED BY

SIGNED HARDY GRAYSONTITLE FIELD FOREMANDATE October 27, 1970

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____



*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963--O-685229
GPO 8 37-499
507-651

RECEIVED

JAN 10 1971

OIL CONSERVATION MAIL
JAN 10 1971