

NO. OF COPIES RECEIVED
DISTRIBUTION
SANTA FE
FILE
U.S.G.S.
LAND OFFICE
OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION

Form O-105
Supersedes Old
O-102 and O-103
Effective 1-4-65

State	Type of Lease
State Oil & Gas Commission	

SUNDY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG SACS IN A DIFFERENT RESERVOIR.
USE MAPPER CATION FOR PERMIT L-1 (FORM O-101) FOR SUCH PROPOSALS.

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER	2. Name of Operator Mobil Oil Corporation	3. Address of Operator P. O. Box 635, Midland, Texas 79701	4. Location of Well UNIT LETTER P, 160 FEET FROM THE East LINE AND 360 FEET FROM THE South LINE, SECTION 24, TOWNSHIP 17-N, RANGE 24-E, N.M.P.M.	5. Elevation (Show whether DT, RT, GK, etc.) 1015	6. County El Paso
---	--	---	---	--	----------------------

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

☐ PERFORM REMEDIAL WORK	☐ PLUG AND ABANDON	☐ REMEDIAL WORK	☐ ALTERING CASING
☐ TEMPORARILY ABANDON	☐ CHANGE PLANS	☐ COMMENCE DRILLING OPS.	☐ PLUG AND ABANDONMENT
☐ PULL OR ALTER CASING	☐ OTHER	☐ CASING TEST AND CEMENT JOB	☐ OTHER

17. Description of Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

BREKING STOPS 12-7, 10,565 FT.

3/16 Finish displ w/ oil, pulled tag, DO's & bit, Schl perf 7" liner in the Upper Abo @ 8495; 8501; 07; 12; 19; 20; 21; 26; 28; 30; 32; 34; 47; 48; & 8549 w/ 1 JSRP, total of 15 holes, ran Howco RITS phr on 2-3/8 tag, reset rot BP @ 9284, tested plug 2000#/ch, set RITS phr @ 8443, swab 35 BLO in 2 hrs, sw dry 4 hrs, BJ Serv acidized Abo perfs 8495-8549 w/ 1000 gals 15% NE acid, TTP 2600 to 3400, rate .8 BPM, ISIP 3200, 5 min 2300, job compl @ 4:30 a.m. 3/16/68, then sw 26 BLO past 1 hr, cont to sw.
Lack 11 BLO + 24 BBN.

3/16 10,565 FT, Upper Abo (8495-8549).
S 11 BLO + 126 BNO + 4 BBN/23 1/2 hrs, 1 hr sw 2 BBLs, S/O 100% oil, 500' FTH, 1/2 ch of gas, unsented phr, pull 2-3/8 tag & phr, ran RITS phr on 2-7/8 FUD End N-60 tag, set phr @ 8450, BJ Serv acid-fractured perfs 8495-8549 w/ 20,000 gals gelled 15% NE acid contained friction reducer & fluid loss additive + 20,000# 20/40 Ottawa sd, TTP 6500 to 7400, rate 16.0 BPM, ISIP 3500, 10 min SIP 3300, job compl 11:50 a.m. 3/17/68. ST, prep to test.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <i>J. J. McDaniel</i>	TITLE <i>Authorized Agent</i>	DATE <i>3-19-68</i>
APPROVED BY <i>[Signature]</i>	TITLE	DATE

CONDITIONS OF APPROVAL, IF ANY: