

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

COPY TO ()

Form approved.
Budget Bureau No. 43-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

New Mexico 04591

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

E. K. Queen Unit TR. 6

9. WELL NO.

16

10. FIELD AND POOL, OR WILDCAT

E. K. Yates 7/Rivers Queen

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 24, T-18-S, R-33-E

12. COUNTY OR PARISH

Lea

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

MOBIL OIL CORPORATION

3. ADDRESS OF OPERATOR

THREE GREENWAY PLAZA EAST - SUITE 800 - HOUSTON, TX 77046

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

990' FSL & 660' FEL Unit P, Section 24, T-18-S, R-33-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3945 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-11-77 - 4500 TD, Queen 4401-49. MIRU DA&S 4/9/77.

4-12-77 - 4500 TD, Queen 4401-49. Ran 4-3/4 bit & CS to 4395, POH, set EZ Drill @ 4342, Knox sqz perfs 4401-49 w/ 50x H to 900 psi, spot 5x on ret, circ to 9.5 MLF, spot 25x 3195-2995 & 1802-1602, LD 37 jts., SDFN.

4-13-77 - 4500 TD, Queen 4401-49. Ran FP, found 5 1/2 free @ 482, cut 5 1/2 @ 483 w/jet cutter, LD 12 jnts. 5 1/2 14# K55, spot 90x plug 533-199, SDFN.

4-14-77 - 4500 TD, Queen 4401-49. Spot 10x 0-26, weld on plate, instl marker, well P&A, rel DA&S 1 PM 4/13/77.

FINAL REPORT.

18. I hereby certify that the foregoing is true and correct

SIGNED

Richard Anderson

TITLE Authorized Agent

DATE

April 25, 1977

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

JUL 13 1979

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side