

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B-1113

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
Marathon Oil Company	Warm State A/C 2
3. Address of Operator	9. Well No.
P. O. Box 220, Hobbs, New Mexico 88240	16
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER N 1650 FEET FROM THE West LINE AND 990 FEET FROM THE South LINE, SECTION 6 TOWNSHIP 18S RANGE 35E NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3977' GL	Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Cement Oil String

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 4820' TD on 3-23-68. Ran 128 jts. of 5-1/2", N-80 casing, Overall Length 4846.64', Effective Length 4805.99', set at 4815.99'. Last setting depth includes Baker float collar and shoe (3.04'), centralizers on bottom 500', and also on 250' from 2750' to 3000'. Dowell cemented 5-1/2" casing with 1400 sacks Trinity Light Weight with 2% Gel, 16# salt per sack, followed by 300 sacks Class "C" Neat. Cement circulated. W.O.C. 18 hrs. Tested casing with 1800# for 30 minutes. Held O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Acting Area Supt. DATE 4-1-68

APPROVED BY [Signature] TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: