

BRIDGES STATE #126
5/10 (18) 6025 dr lm 8-3/4" hole, 1 1/4 @ 5948. Fr wtr.

BRIDGES STATE #126
5/11 (19) 6375 drlg lm, 8-3/4" hole, 1 1/2 @ 6329. Fr wtr.

5/13 (21) 6935 drlg lm & sh, 8-3/4" hole, 1 1/4 @ 6773. Fr wtr.

BRIDGES STATE #126
5/14 (22) 7240 drlg lm & sh, 8-3/4" hole, 1 1/2 @ 7056. Fr wtr.

BRIDGES STATE #126
5/15 (23) 7440 drlg lm & sh, 8-3/4" hole, 3/4 @ 7415. Fr wtr.

BRIDGES STATE #126
5/16 (24) 7685 drlg dolo & sh, 8-3/4" hole, NND. Fr wtr.

BRIDGES STATE #126
5/17 (25) 7980 drlg lm & sh, 8-3/4" hole, 1° @ 7723. Fr wtr.

BRIDGES STATE #126
5/18 (26) 8240 drlg dolo & sh, 8-3/4" hole, 1 1/4° @ 8037. Fr. wtr.

5/20 (28) 8985 drlg lm & sh, 8-3/4" hole, 1° @ 8672. Fr. wtr.

BRIDGES STATE #126
5/21 (29) 9225 drlg lm & sh, 8-3/4" hole, 1 1/2° @ 9105. 8.5-34-12.0.
Started mudding up @ 9105.

BRIDGES STATE #126
5/22 (30) 9385 drlg lm, ch, & sh, 8-3/4" hole, NND. 8.5-38-8.0 1% oil.

BRIDGES STATE #126
5/23 (31) 9550 drlg lm & sh, 8-3/4" hole, 1-3/4° @ 9338. 8.5-38-8.0 2 1/2% oil.

BRIDGES STATE #126
5/24 (32) 9635 drlg dolo & sh, 8-3/4" hole, 1° @ 9623. 8.5-38-8.0 3% oil.

BRIDGES STATE #126
5/25 (33) 9875 drlg dolo & sh, 8-3/4" hole, NND. 8.5-37-8.0, 3% oil.

5/27 (35) 10,250 drlg lm, sh & ch, 8-3/4" hole, 1 1/2 @ 9922. 8.5-37-8.0, 3% oil.

BRIDGES STATE #126
5/28 (36) 10,350 drlg lm & sh, 8-3/4" hole, 1 1/2 @ 10,326. 8.6-37-8.0, 6% oil.

BRIDGES STATE #126
5/29 (37) 10,515 drlg lm & sh, 8-3/4" hole. NND. 8.6-38-6.4, 6% oil.

BRIDGES STATE #126
5/31 (39) 10,800 drlg lm, ch & sh, 8-3/4" hole. 3/4 @ 10,548. 8.6-37-7.0, 5% oil.

BRIDGES STATE #126
6/1 (40) 10,890 drlg lm & sh, 8-3/4" hole, 1/4° @ 10,886. 8.6-38-7.0 5% oil.

6/3 (42) 11,245 drlg lm, sh & ch, 8-3/4" hole, NND. 8.6-37-8.0 4% oil.

BRIDGES STATE #126
6/4 (43) 11,365 drlg lm & sh, 8-3/4" hole, 1 1/4° @ 11,280. 8.6-37-7.8, 4% oil.

BRIDGES STATE #126
6/5 (44) 11,490 drlg lm & sh, 8-3/4" hole, NND. 8.6-37-7.0, 4% oil.

BRIDGES STATE #126
6/6 (45) 11,640 drlg lm & sh, 8-3/4" hole, NND. 8.6-37-7.8, 3% oil.

BRIDGES STATE #126
6/7 (46) 11,790 drlg lm & sh, 8-3/4" hole, NND. 8.7-38-7.0, 3% oil.