

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-025-22627

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.  
25697

7. Lease Name or Unit Agreement Name  
W.D. Grimes (NCT-A)

8. Well No. 16

9. Pool name or Wildcat  
Hobbs: Upper Blinbry

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator  
Texland Petroleum - Hobbs, L.L.C.

3. Address of Operator  
777 Main Street, Ste. 3200  
Fort Worth, Tx. 76102

4. Well Location

Unit Letter D : 800 feet from the North line and 700 feet from the West line

Section 32 Township 18S Range 38E NMPM County Lea

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3636

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOBS ☐

CONDITIONS OF APPROVAL

All pits must be lined with plastic

All shoe plugs, stub plugs & cement plugs above perforations must be tagged

All cement plugs pumped minimum 25 sxs & be minimum 100 feet

C-103 plugging plan was approved on March 12, 2002. Texland would like to request an extension for plugging deadline for this well. Texland will have this well plugged prior to July 1, 2002.

Current PBTD 5140'

1. Circulate hole w/ 9.5 ppg brine water with 25# of gel per bbl.

2. 25sx Class C cement (1/2 above & 1/2 below) across bottoms of unitized Grayburg/ San Andres at 4200'

3. 25sx Class C cement (1/2 above & 1/2 below) across top of unitized Grayburg/San Andres at 3700' — TAG

4. 25sx Class C cement (1/2 above & 1/2 below) across top of Yates at 2635.

5. 25 sx Class C cement (1/2 above & 1/2 below) across 9 5/8" casing shoe at 1497'

6. Tag plug at 1447' - 1547'

7. Spot 10sx (60') Class C cement plug at surface

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ann Burdette TITLE Regulatory Analyst

DATE 04/02/2002

Type or print name Ann Burdette

(This space for State use)

APPROVED BY

Conditions of approval, if any:

ORIGINAL SIGNED BY  
GARY W WINK  
OC FIELD REPRESENTATIVE II/STAFF MANAGER  
TITLE

APR 09 2002  
Telephone No. (817)336-2751

DATE

APR 09 2002