

COUNTY LEA FIELD Undesignated STATE NM 30-025-22792
 OPER GULF OIL CORP. MAP
 17 Grimes, W. D. (NCT-A)
 Sec. 32, T-18-S, R-38-E CO-ORD
 660' ENL, 1980' FWL of Sec.
 Spd 10-19-68
 Cmp 11-27-68

	CLASS			
	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING				
13 3/8" at 366' w/370 sx				
9 5/8" at 3399' w/1450 sx				
7" at 6149' w/545 sx				
LOGS EL GR RA IND HC A				
	TD 6150'; PBD 5970'			

IP (Blinebry) Perf 5780-5949' S 160 BOPD. Pot based on 12 hr test of 80 BO

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Moran PROP DEPTH 6200' TYPE
 DATE

F.R. 10-17-68
 PB 6200' (Blinebry)
 Contractor - Moran
 10-18-68 Drlg. 3400'
 11-4-68 TD 4530'; On Trip
 Lost returns @ 4530'
 11-11-68 Drlg. 5705' dolo
 Set 4 cement plugs
 11-18-68 TD 6150'; PBD 6100'; MO Rotary
 11-23-68 TD 6150'; PBD 5970'; Prep test
 Perf @ 5994', 5996', 6080', 6082'
 Acid (5994-6082') 300 gals
 Swbd load + 32 BFW w/trace oil (5994-6082')
 BP @ 6074'
 Acid (5994-96') 750 gals
 Swbd 34 BO + 81 BFW in 5 hrs (5994-96')

LEA
GULF CIL CORP. #17 Grimes, W. D. (NCT-A)

Undesignated

NM Sec 32-18S-38E
Page 2

11-25-68

Continued

Acid (5994-96') 750 gals

Swbd 120 BW (5994-96')

Ret @ 5970'

Sqzd (5994-6082') 150 sx

Perf 5780-82', 5858-60', 5880-82', 5898-5900',
5947-49'

Acid (5898-5900') 4000 gals

12-2-68

TD 6150'; PBD 5970'; COMPLETE

LOG TOPS: Anhydrite 1474', Yates 2703', Queen
3357', San Andres 4012', Glorieta 5347',
Blaine 5770'

12-5-68

COMPLETION REPORTED

COUNTY	LEA	FIELD	Undesignated	STATE	NM 30-025-22792
OPR	GULF OIL CORP.				MAP
17 Grimes, W. D. (NCT-A)					
Sec. 32, T-18-S, R-38-E				CO-ORD	
660' FNL, 1980' FWL of Sec.					
Spd 10-19-68		CLASS			
Cmp 11-27-68		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
13 3/8" at 366' w/370 sx					
9 5/8" at 3399' w/1450 sx					
7" at 6149' w/545 sx					
LOGS EL GR RA IND HC A					
		TD 6150'; PBD 5970'			
IP (Blinebry) Perf 5780-5949' S 160 BOPD. Pot based on 12 hr test of 80 BO					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Moran	PROP DEPTH	6200'	TYPE
DATE				

	F.R. 10-17-68
	PD 6200' (Blinebry)
	Contractor - Moran
10-28-68	Drlg. 3400'
11-4-68	TD 4530'; On Trip
	Lost returns @ 4530'
11-11-68	Drlg. 5705' dolo
	Set 4 cement plugs
11-18-68	TD 6150'; PBD 6100'; MO Rotary
11-25-68	TD 6150'; PBD 5970'; Prep test
	Perf @ 5994', 5996', 6080', 6082'
	Acid (5994-6082') 300 gals
	Swbd load + 32 BFW w/trace oil (5994-6082')
	BP @ 6024'
	Acid (5994-96') 750 gals
	Swbd 34 BO + 81 BFW in 5 hrs (5994-96')

LEA
GULF OIL CORP. #17 Grimes, W. D. (NCT-A)

Undesignated

NM Sec 32-18S-38E
Page 2

11-25-68

Continued

Acid (5994-96') 750 gals

Swbd 120 BW (5994-96')

Ret @ 5970'

Sqzd (5994-6082') 150 sx

Perf 5780-82', 5858-60', 5880-82', 5898-5900',
5947-49'

Acid (5898-5900') 4000 gals

12-2-68

TD 6150'; PBD 5970'; COMPLETE

LOG TOPS: Anhydrite 1474', Yates 2708', Queen
3357', San Andres 4012', Glorieta 5347',

Blindbry 5770'

12-5-68

COMPLETION REPORTED