

COUNTY LEA FIELD Wildcat STATE NM 30-025-22795

OPR AZTEC OIL & GAS CO. MAP

1 State NG

Sec 24, T-18-S, R-36-E

1980' FNL, 1980' FEL of Sec.

Spd 10-12-68 CO-ORD

Cmp 11-22-68

CSG & SX - TUBING	FORMATION		CLASS	
	FORMATION	DATUM	FORMATION	DATUM
8 5/8" at 353' w/240 SX				
5 1/2" at 5673' w/400 SX				

LOGS EL GR RA IND HC A

IP (San Andres) Perf 4876-5030' P 66 BOPD. Pot based on 24 hr test, GOR 800, Grav 38.

TD 5700'; PBD 5068'

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

PROP DEPTH 5800' TYPE

10-15-68 F.R. 10-17-68
 10-22-68 PD 5800' - San Andres
 Drlg. 3260' salt
 TD 4970'; Prep drill
 DST 4871-4970', open 1 hr 30 mins, rec 240'
 VSGCDM, 1 hr ISIP 966#, FP 157-185#, 2 hr
 30 min FSIP 1981#
 10-28-68 TD 5700'; MO Rotary
 DST 5170-5270', open 1 hr 30 mins, rec 420' DM,
 1 hr ISIP 2027#, FP 80-282#, 1 hr FSIP 1887#
 11-4-68 TD 5700'; PBD 5070'; Swbg
 Perf 5520-30', 5540-50', 5570-5600' w/1 SPF
 Acid (5520-5600') 2000 gals
 Swbd 100% wtr (5520-5600')
 Set BP @ 5400'

LEA NM Wildcat
AZTEC OIL & GAS CO. #1 State NG

Sec 24-18S-
Page 2

11-4-68 Continued
Perf 5240-60' w/1 SPF
Acid (5240-60') 2000 gals
Swbd 1 B salt wtr PH (5240-60')
Set BP @ 5070'
Perf 4876-96', 4908-18', 4940-50'
Acid (4876-4950') 2000 gals
Swbd 30 BLW w/good show oil & gas
TD 5700'; PBD 5070'; RU Pmp
Swbd dry (4876-4950')
Acid (4876-4950') 5000 gals
Swbd 2 BOPH
TD 5700'; PBD 5070'; TO Pmp
11-11-68 Ppd 31 BO + 3-4 BLW in 24 hrs, GOR 1400
11-18-68 (4876-4950')

11-25-68 TD 5700'; PBD 5070'; Prep TO Pmp
Perf 5014-30' w/2 SPF
Acid (5014-30') 2000 gals
Frac (4876-5030') 50,000 gals wtr + 50,000# sd
12-4-68 TD 5700'; PBD 5070'; WO Pot
Ppd 66 BO + 60 BLW in 24 hrs, GOR 800
12-9-68 TD 5700'; PBD 5070'; COMPLETE
LOG TOPS: Anhydrite 1680', Queen 4002',
San Andres 4855'
12-12-68 COMPLETION REPORTED