

COUNTY IEA FIELD Undesignated STATE NM 30-025-22869
 OPR AZTEC OIL & GAS CO. MAP
 1 Catron - State CO.ORD

Sec 12, R-18-S, R-36-E
 810' ENL, 1980' FEEL of Sec.

Spd 11-7-68

Cmp 3-11-69

CSG & SX TUBING

8 5/8" at 350'

5 1/2" at 5229' w/250 SX.

LOGS EL GR RA IND HC A

TD 5230'

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus
 DATE

PROP DEPTH 5200' TYPE

12-9-68 F.R. 11-28-68; Opr's Elev. 3792' DF
 12-17-68 PD 5200' (San Andres)
 12-23-68 Contractor - Cactus
 1-7-69 Drig. 1250'
 Drig. 3935'
 TD 5230'; Prep Run Casing
 TD 5230'; TO Pmp
 Perf 5156-82'
 Acid (5156-82') 1000 gals
 Perf 5206-16'
 Acid (5206-16') 500 gals
 Ppd 200 BW w/trace oil in 24 hrs (5156-5216')
 1-14-69 TD 5230'; TO Pmp
 Perf 5096-5106'
 Swbd 2 EO + 10 BW, Swbd dry (5096-5106')

IEA
AZTEC OIL & GAS CO.

Undesignated

NM Sec 12, T18S, R36E
1 Catron-State
Page #2

1-14-69

Continued

Ppd 125 BW w/show oil & gas in 16 hrs
(5096-5216')

1-22-69

TD 5230'; TO Pmp

1-27-69

Ppd 12 BO + 200 BW in 24 hrs (5096-5216')

TD 5230'; Swog

Sqzd (5096-5106') 2.40 oz

Perf 5052-80', 5052-80' 1000 gals

Acid (5052-80') 1000 gals

Swbd approx. 8 BO in 24 hrs

2-3-69

TD 5230'; TO Pmp

2-17-69

Ppd 3 BO + 20 BW in 24 hrs (5052-80')

2-24-69

TD 5230'; TO Pmp

TD 5230'; Ppg load

2-24-69

Continued

Packed off (Perfs 5052-80') w/moth balls

Perf 4955-60', 4970-75', 4996-5006' w/1 SPF

Acid (4955-5006') 3000 gals

TD 5230'; Ppg load

3-3-69

TD 5230'; TO Pmp

3-10-69

TD 5230'; Temp. Aban.

3-17-69

TD 5230'; TEMPORARILY ABANDONED

3-24-69

LOG TOP: San Andres 4950'

3-27-69

COMPLETION REPORTED