

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. OG 1633	
7. Unit Agreement Name None	
8. Farm or Lease Name Continental-State	
9. Well No. 4	
10. Field and Pool, or Wildcat Undesignated	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	
2. Name of Operator Triton Oil & Gas Corp.	
3. Address of Operator 2626 Republic Bank Tower, Dallas, Texas 75201	
4. Location of Well UNIT LETTER C , 990 FEET FROM THE North LINE AND 1650 FEET FROM THE West LINE, SECTION 23 TOWNSHIP 18 S RANGE 34 E NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.) 3993.9' GR	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>				
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>				
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>				

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Surface Casing

Ran 8-5/8" O.D., 20#, casing to 410'.

Cemented with 275 sacks Regular Cement with 2% Calcium Chloride at 410'. Cement circulated-W.O.C. 18 hrs. - Nippled up, installed blow out preventer, pressured up to 1000 psi, for 30 minutes, no drop in pressure - casing okay. Completed 1-4-69.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

NED _____ TITLE **Petroleum Engineer** DATE **January 16, 1969**
 BY *[Signature]* _____ TITLE _____ DATE _____
 IONS OF APPROVAL, IF ANY: