

IP (San Andres) Perf 4992-5104' P 61 EOPD + 60 BW. Pot based on 24 hr test. GOR 750; Grav 36.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Cactus Drlg. Co.	PROP. DEPTH	5200'	TYPE
DATE				

F.R. 12-12-68
PD 5200' (San Andres)
Contractor - Cactus Drilg. Co.
2-6-69 AMEND FIELD NAME, Formerly reported as
Undesignated
1-7-69 TD 5200'; WOC
Corad 5060-5116', rec 56' dolo, bldg oil & gas
1-14-69 TD 5200'; PED 5141'; Prep TO Pmp
Perf 4992-98', 5006-12', 5026-32',
5036-42', 5055-61', 5076-80', 5098-5104'
w/1 SPF
Acid (4992-5104') 5000 gals
Swbd 25 RO + 125 ELW in 10 hrs
1-22-69 TD 5200'; PED 5141'; TO Pmp
Ppd 30 RO + 60 BW in 24 hrs
1-27-69 TD 5200'; PED 5141'; WO Potential
Ppd 61 RO + 60 BW in 24 hrs

LEA Arkansas Junction NM Sec 12,T18S,R36E
AZTEC OIL & GAS CO. 1 Gulf State Page #2

2-3-69

TD 5200'; PSD 5141'; COMPLETE
LOG TOPS: Anhydrite 1750', Queen 4035',
San Andres 4916'

2-6-69

COMPLETION REPORTED