

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Gulf Oil Corporation	8. Farm or Lease Name V. D. Crimes (MCT-A)
3. Address of Operator Box 670, Hobbs, New Mexico 88240	9. Well No. 19
4. Location of Well UNIT LETTER E , 1730 FEET FROM THE North LINE AND 330 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 18-S RANGE 35-E NMFM.	10. Field and Pool, or Wildcat Hobbs Blinebry
15. Elevation (Show whether DF, RT, GR, etc.) 3636' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moran Drilling Company spudded 17-1/2" hole at 8:00 AM, February 17, 1969. Drilled to 350'. Ran 10 joints, 328' of 13-3/8" 43# H-40 casing set and cemented at 342' with 300 sacks of Class C with 2% Ca Cl2. Cement did not circulate. Cemented thru 1" pipe with 75 sacks of Class C with 2% Ca Cl2. Cement circulated. WOC & MU 18 hours. Tested casing with 1400#, 30 minutes. OK.

Started drilling 11" hole at 350' at 1:00 PM, February 18, 1969.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY
SIGNED C. D. BORLAND TITLE Area Production Manager DATE February 18, 1969

APPROVED BY John W. Runyan TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____