

(14) Petroleum Information.

COMPANION
A Member of A.C. Baker Company

© U.S. Government Reproduction Prohibited

COUNTY LEA FIELD Hobbs STATE NM
 OPR GULF OIL CORP. MN-23007
 NO 19 LEASE Grimes, W. D. (NCT-A) SERIAL OWWO
Sec 32, T-18-S, R-38-E MAP
1730' FNL, 330' FWL of Sec CO-ORD
Hobbs Townsite ELEV 5685' LBS

SPD Re- 2-17-75 WELL CLASS: DX FIN DO
 CSE

FORMATION	DATUM	FORMATION	DATUM
13 3/8" at 342' w/300 SX			
8 5/8" at 3811' w/500 SX			
5 1/2" at 6050' w/455 SX			

 TD 6051' (ELBR) PBD 5685'

IP (San Andres) Perfs 4158-4230' P 39 BOPD + 138 BW. Pot based on 24 hr test. GOR NR; Grav NR

CONTR OPR'S ELEV 3636' GL PD 4230' WO

F.R.C. 3-29-75
 (San Andres)
 (Orig. comp 5-20-69 thru (Blinbry) Perf 5956',
 OTD 6051', OPB 6023')
 3-24-75 TD 6051'; PBD 5685'; COMPLETE
 PB TO 5685'
 Perf 4158-60', 4180-82', 4205-07', 4228-30' w/4
 SPF
 Acid (4158-4230') 4750 gals
 3-29-75 COMPLETION REPORTED

COUNTY LEA FIELD Hobbs STATE NM 30-025-23007

OPR GULF OIL CORP. MAP

19 Grimes, W. D. NCI-A

Sec 32, T-18-S, R-38-E

CO-ORD

1730' FNL, 330' FWL of Sec.

Spd 2-17-69

CLASS

EL

Cmp 5-20-69

FORMATION

DATUM

FORMATION

DATUM

CSG & SX - TUBING

13 3/8" at 342' w/300 sx

8 5/8" at 3811' w/500 sx

5 1/2" at 6051'

LOGS EL GR RA IND HC A

TD 6051'; PBD 6023'

IP (Blinebry) Perf 5956' P 29 BOPD + 31 BLW. Pot based on 10 hr test.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Moran Drlg. Co.

PROP DEPTH 6100'

TYPE

DATE

2-18-69

2-25-69

3-4-69

3-11-69

3-18-69

F.R. 2-18-69

PD 6100' (Blinebry)

Contractor - Moran Drlg. Co.

Drlg. 350'

Drlg. 4255'

TD 6051'; PBD 6029'; Prep Perf

TD 6051'; PBD 6029'; WOC

Perf 5758-60', 5805-07', 5847-49', 5870-72',

5899-5901', 5921-23' w/2 SPF

Acid (5758-5923') 4200 gals (15%)

Swbd 67 BW in 10 hrs (5758-5923')

Sqzd (5758-5923') w/125 sx

TD 6051'; PBD 6029'; SI

Perf 5775-77', 5832-34', 5880-82', 5925-27'

w/2 SPF

Acid (5775-5927') 1000 gals

3-18-69 Continued
Swbd load + 18 BW (5775-5927')
Swbd 12 BW (5925-27')
Acid (5925-27') 750 gals (had Communications)
3-24-69 TD 6051'; PBD 6029'; Prep Acid
Swbd 132 BW in 15 hrs (5832-5927')
Swbd 48 BW in 13 hrs (5775-77')
Sqzd (5775-5927') w/200 sx
Perf 5864-74' w/2 SPF
Swbd dry (5864-74')
4-1-69 TD 6051'; PBD 5878'; Swbg
Acid (5864-74') 750 gals
Swbd dry (5864-74')
Frac (5864-74') 122 BW + 3800# sd

4-1-69 Continued
Swbd load + 36 BW in 11 hrs (5864-74')
4-22-69 TD 6051'; PED 5878'; SI
4-28-69 TD 6051'; PBD 5878'; WOC
Sqzd (5864-74') w/125 sx
5-6-69 TD 6051'; PBD 6023'; Swbg
Perf @ 5956' w/4 shots
Acid (5956') 3000 gals
Swbd 12 BO + 17 BW in 24 hrs
5-12-69 TD 6051'; PBD 6023'; Prep TO Pmp
Swbd 12 BO + 20 BW in 24 hrs
5-19-69 TD 6051'; PBD 6023'; TO Pmp
5-26-69 TD 6051'; PBD 6023'; COMPLETE
LOG TOPS: Anhydrite 1440', Yates 2668',
Queen 3380', San Andres 4030', Glorieta
5350', Blinbry 5750'
5-29-69 COMPLETION REPORTED