

COUNTY LEA FIELD Hobbs STATE NM 30-025-23022
 OPR HUMBLE OIL & REFG. CO. MAP
28 Bowers "A" Federal
Sec 29, T-18-S, R-38-E CO-ORD
660' FSL, 990' FWL of Sec.

Re-Cmp 5-8-69	CLASS		EL	
	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING				
11 3/4" at 373' w/300 sx				
8 5/8" at 3849' w/500 sx				
5 1/2" at 5989' w/450 sx				
LOGS EL GR RA IND HC A				

TD 6000'; PED 5958'
 (Plinebry) Perfs 5856-5928' NO CHANGE.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT
 DATE PROP DEPTH 5452' TYPE WO

6-2-69 F.R.C. 6-5-69; Opr's Elev. 3650' DF
 PD 5452' WO (Glorieta)
 (Orig. comp 4-15-69 thru Perfs 5856-5928',
 OTD 6000', OPB 5958')
 TD 6000'; PED 5958'; COMPLETE
 Perf 5433-35', 5439-42', 5449-52' w/1 SPF
 Acid (5433-52') 500 gals
 Swbd AW w/small amt of oil (5433-52')
 Sqzd (5433-52') w/55 sx
 Perf 5376-81', 5384-86', 5392-98', 5400' w/1 SPF
 Acid (5376-5400') 500 gals
 Acid (5376-5400') 1500 gals
 Swbd lead & formation wtr (5376-5400')
 Sqzd (5376-5400') w/75 sx
 6-5-69 COMPLETION REPORTED

COUNTY LEA FIELD Hobbs STATE NM 30-025-23022

OPR HUMBLE OIL & REFC. CO. MAP

28 Bowers "A" Federal

Sec 29, T-18-S, R-38-E CO-ORD

660' FSL, 990' FWL of Sec.

Spd 3-12-69

Cmp 4-15-69 CLASS

	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING				
11 3/4" at 373' w/300 sx				
8 5/8" at 3849' w/500 sx				
5 1/2" at 5989' w/450 sx				
LOGS EL GR RA IND HC A				
	TD 6000'; PBD 5958'			
IP (Blinbry) Perf 5856-5928' P 266 BOPD + 144 BW. Pot based on 10 hr test. GOR 197; Grav 36.				

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. FROP DEPTH 6400' TYPE

DATE

	F.R. 2-25-69
	PD 6400' (Blinbry)
3-17-69	Drilg. 1417' redbed
3-24-69	TD 3850'; Prep Drill
3-31-69	TD 5880'; Prep Core
	Cored 5370-99', rec 22' dolo, lm & sd,
	shly anhy, scattered bldg oil & gas
	Cored 5520-59', rec 39' dolo, scattered bldg
	oil & gas
	Cored 5830-80', rec 50' dolo, anhy dolo &
	shly sd, scattered bldg oil & gas
4-7-69	TD 6000'; PBD 5958'; WOC
	Cored 5880-5917', no description
	Cored 5917-5951', no description

4-14-69 TD 6000'; PBD 5958'; RU Pmp
Perf 5856-58', 5860-62', 5874-76',
5880-82', 5897-5900', 5925-28'
Acid (5856-5928') 500 gals
Swbd 150 BO + 109 BW in 11 hrs
4-21-69 TD 6000'; PBD 5958'; COMPLETE
LOG TOPS: Anhydrite 2613', San Andres 3983',
Glorieta 5341', Blinbry 5740'
4-24-69 COMPLETION REPORTED