

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION O. C. C.

APR 22 11 35 AM '69

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
<b>A-1469</b>

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>Amerada Petroleum Corporation</b>	8. Farm or Lease Name <b>State "A"</b>
3. Address of Operator <b>P. O. Box 668 - Hobbs, New Mexico</b>	9. Well No. <b>4</b>
4. Location of Well UNIT LETTER <b>B</b> , <b>660</b> FEET FROM THE <b>North</b> LINE AND <b>2130</b> FEET FROM THE <b>East</b> LINE, SECTION <b>32</b> TOWNSHIP <b>18S</b> RANGE <b>38E</b> N.M.P.M.	10. Field and Pool, or Wildcat <b>Undesignated</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3654' DF 3642' GL</b>	12. County <b>Lea</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

### SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to TD of 6000'. Ran 5 1/2" 15.5#, K-55 liner set at 5998" with liner hanger at 3695'. Cemented liner with 165 sacks Class "C" cement with 4% gel and 1/4# cello flake per sack and 160 sacks Class "C" cement, a total of 325 sacks. Displaced plug to 5929' at 8:58 a.m. April 18, 1969. Reversed out 32 sacks cement at 3590'. Tested 5 1/2" liner at 3:30 a.m. April 19, 1969 with 1000#, held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED 

TITLE **District Superintendent**

DATE **April 21, 1969**

APPROVED BY 

TITLE **APPROVED**

DATE **APR 22 1969**

CONDITIONS OF APPROVAL, IF ANY: