

|                          |                             |           |       |           |       |              |
|--------------------------|-----------------------------|-----------|-------|-----------|-------|--------------|
| COUNTY                   | LEA                         | FIELD     | Hobbs | STATE     | NM    | 30-025-23081 |
| OPR                      | GULF OIL CORP.              |           |       |           |       | MAP          |
|                          | 5 Graham-State (NGI-A)      |           |       |           |       |              |
|                          | Sec 24, T-18-S, R-37-E      |           |       |           |       | CO-ORD       |
|                          | 1980' FNL, 760' FEL of Sec. |           |       |           |       |              |
|                          | Spd 3-24-69                 |           |       |           |       | CLASS        |
|                          | Cmp 5-26-69                 |           |       |           |       | EL 36748     |
|                          |                             | FORMATION | DATUM | FORMATION | DATUM |              |
| CSG & SX - TUBING        |                             |           |       |           |       |              |
| 13 3/8" at 408' w/400 sx |                             |           |       |           |       |              |
| 8 5/8" at 3903' w/500 sx |                             |           |       |           |       |              |
| 5 1/2" at 6106' w/385 sx |                             |           |       |           |       |              |
|                          |                             |           |       |           |       |              |
|                          |                             |           |       |           |       |              |
| LOGS EL GR RA IND HC A   |                             |           |       |           |       |              |
|                          | TD 6107'                    |           |       |           |       |              |
| PLUGGED & ABANDONED      |                             |           |       |           |       |              |

Distribution limited and publication prohibited by subscribers' agreement.  
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

|       |            |       |      |
|-------|------------|-------|------|
| CONT. | PROP DEPTH | 6700' | TYPE |
| DATE  |            |       |      |

F.R. 3-25-69  
 PD 6700' (Blinebry)  
 3-25-69 TD 442'; Rng Casing  
 4-1-69 ID 3904'; WOC  
 4-8-69 TD 5930'; Prep Core  
 Lost Circ @ 4620'  
 4-15-69 TD 6107'; PED 6086'; MORT  
 Cored 5930-79', rec 49', no description  
 Cored 5979-6029', rec 50', no description  
 Cored 6029-77', rec 48', no description  
 4-22-69 TD 6107'; PED 6086'; SI  
 Perf 6008-10' w/4 SPF  
 Acid (6008-10') 500 gals  
 Swld 3 EO + 167 BW in 24 hrs

4-28-69 TD 6107'; PED 6086'; TO Pmp  
Ppd 147 BW in 24 hrs  
5-6-69 TD 6107'; PED 6086'; TO Pmp  
Ppd 443 BW in 24 hrs (6008-10')  
5-12-69 TD 6107'; PED 6086'; Swbg  
Sqzd (6008-10') w/150 sx  
Perf @ 5960' w/4 shots  
Acid (5960') 1000 gals  
Swld 194 BW in 24 hrs (5960')  
5-19-69 TD 6107'; PED 5885'; Swbg  
Perf 5198-5203' w/4 SPF  
Perf 5526-28', 5543-45', 5573-75' w/4 SPF  
Acid (5526-75') 1000 gals (157)  
Swld 12 BW in 11 hrs

5-27-69 TD 6107'; PED 5885'; Plugged & Abandoned  
Swld 1 1/2 BW & swld dry (5526-75')  
Perf 5320-22'  
Swld 20 BW & swld dry (5320-22')  
Acid (5320-22') 1000 gals  
Swld 84 BW w/trace oil (5320-22')  
6-2-69 TD 6107'; PLUGGED & ABANDONED  
6-5-69 COMPLETION REPORTED