

| | |
|------------------------|--|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

MAY 7 12 18 PM '69

| |
|--|
| Indicate Type of Lease State AM Fee <input type="checkbox"/> |
| 5. State Oil & Gas Lease No. |
| 1-1469 |
| 7. Unit Agreement Name |
| 8. Farm or Lease Name |
| 9. Well No. State "A" |
| 10. Field and Pool, or Wildcat Undesignated |
| 12. County |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER- **Drilling**

2. Name of Operator
Amerada Petroleum Corporation

3. Address of Operator
Box 668, Hobbs, New Mexico

4. Location of Well
UNIT LETTER **A**, **660** FEET FROM THE **North** LINE AND **660** FEET FROM
THE **East** LINE, SECTION **32**, TOWNSHIP **18-S**, RANGE **38-E** NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
DF 3660' GL 3649'

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

| | | | |
|--|---|---|---|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | OTHER <input type="checkbox"/> | CASING TEST AND CEMENT JOB <input type="checkbox"/> | |

SUBSEQUENT REPORT OF:

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 11" hole to 3800'. Ran 1413' of 8-5/8" OD 32# J-55 Casing and 2385' of 8-5/8" OD 24# J-55 Casing W/Guide Shoe on bottom and float collar at 3731'. Set at 3798' with 390 ex lite wate ~~mix~~ cement and 200 ex Class C incore cement. Pumped plug to 3731' at 5:45 AM 5-2-69. 18 hrs W.O.C. Tested casing for 1/2 hr W/1000#. Held OK. Top cement outside 8-5/8" Casing at 2300'. Started drilling 7-7/8" hole at 4:30 AM 5-3-69

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *[Signature]* TITLE Dist Supt. DATE 5-3-69
APPROVED BY *[Signature]* TITLE DATE MAY 7 1969
CONDITIONS OF APPROVAL, IF ANY: