Form 9-331
(May 1965)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLIC •
(Other instructions (&
verse side)

Form approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.
NM-O1135

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1.
OIL WELL [X]   GAS WELL [ ]   OTHER

7. UNIT AGREEMENT NAME
PLAINS UNIT FED

2. NAME OF OPERATOR
Amoco Production Company

8. FARM OR LEASE NAME

3. ADDRESS OF OPERATOR
BOX 68, HOBBS, N. M. 88240

9. WELL NO.
9

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

10. FIELD AND POOL, OR WILDCAT
LUSK-DELAWARE

1980' FNL x 1980' FWL Sec. 33 (UNIT F, SE/4 NW/4)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
33-19-32 N.M.P.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3553' R.D.B.

12. COUNTY OR PARISH | 13. STATE
LEA | **N.M.**

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]	WATER SHUT-OFF	[ ]	REPAIRING WELL [ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]	FRACTURE TREATMENT	[ ]	ALTERING CASING
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]	SHOOTING OR ACIDIZING	[ ]	ABANDONMENT* [X]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]	(Other)		
(Other)						

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Well was physically abandoned 2-26-73.
Plugged as follows:

Spotted 25 Sx cement plug 4809 - 4515'.
Shot & pulled 4½" casing from 3553'.
Spotted 30 Sx cement plug (in & out 2 4½" stub @ 3553'.
"   75 Sx   "   "   3080 - 2861'.
"   270 Sx @ "Surface"   2600 - 750'.
"   10 Sx @ Surface & erect P & A marker.

Final cleanup shall be made and ground restored to contour.
All intervals filled w/ mud laden fluid.

10¾" CSA 323 Cir.
7⅝" CSA 2603 Cir.
4½" CSA 5150'

18. I hereby certify that the foregoing is true and correct

SIGNED _____   TITLE **AREA SUPERINTENDENT**   DATE **MAR 1 1973**

(This space for Federal or State office use)

APPROVED BY _____   TITLE _____   DATE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
MAR 25 1974
ARTHUR R. BROWN
DISTRICT ENGINEER

0+4- USGS-11
1- DIV
1- SUSP
1- RRC
1- MOBIL-MIDLAND

*See Instructions on Reverse Side