DISTRIB		-		Form C-103
	S RECEIVED	40800		Supersedes Old
	UTION	NEW MENICO PHI CON	OF THE ONL COMMISSION	C-102 and C-103 Effective 1-1-65
SANTA FE		NEW MEXICONIA 2	SER TOUR BEST OF FICE O. C. C	*
U.S.G.S.		<i>J</i>	2 C L C C C C C C C C C C	5a. Indicate Type of Lease
LAND OFFIC	CE		STANKS I 47 AN '6	State X Fee.
DISTRIBUTION SANTA FE FILE U.S.G.S. LAND OFFICE OPERATOR NO. OF COPIES RECEIVED NEW MEXICOPIL CONSERVICITION COMMUSSION C. C. C. 2 52 MANAGE 1 47 AN 65				5. State Oil & Gas Lease No.
				E - 1251
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)				
OIL X	GAS WELL 0	THER-		7. Unit Agreement Name
2. Name of Operator Pennzoil United, Inc. 3. Address of Operator				8. Form or Lease Name Mobil "7" State
				9. Well No.
_	P. O.	Drawer 1828 - Midlan	d, Texas 79701	1
4. Location of \	p 660	FEET FROM THE North	LINE AND 1930 FEET F	10. Field and Pool, or Wildcat Undesignated
	East Line, section	- 17 <i>c</i>		MPM.
15. Elevation (Show whether DF, RT, GR, etc.)				12. County
				Lea
	Spudded well at 4 casing to 348'	1:00 P.M Drilled - Cemented w/250 sx (17 1/2" hole to 348'. : Class "H" 6% gel plus	ding estimated date of starting any propos - Ran 13 3/8" OD, 48# 100 sx Class "H" 2% CaCl.
	Plug down at 11:45 P.M Cement circulated After 20 hrs, tested casing w/1,000# for 30 min Tested 0.K.			
5-4-69	After 20 hrs, tes	ited casing w/1,000#	for 30 min Tested	O.K.
5-4-69 5-12-69	Orilled 11" hole w/664 sx Class "H 150 sx Class "H"	to 4304' Ran 8 5/	/8" OD, 24# & 32# casi el w/16.5# salt & 1/4# ocele per sack. Plug d	
5-12-69	Orilled 11" hole w/664 sx Class "H 150 sx Class "H" temperature surve	to 4304' Ran 8 5/ 1" 50/50 posmix 6% go w/8# salt & 1/4# flo ey Top cement at 2	/8" OD, 24# & 32# casi el w/16.5# salt & 1/4# ocele per sack. Plug d	ng to 4304'. Cemented flocele per sack plus own at 11:00 A.M Ran
5-12-69	Orilled 11" hole w/664 sx Class "H 150 sx Class "H" temperature surve	to 4304' Ran 8 5/ 1" 50/50 posmix 6% go w/8# salt & 1/4# flo ey Top cement at 2	/8" OD, 24# & 32# casi el w/16.5# salt & 1/4# ocele per sack. Plug do 2390'.	ng to 4304'. Cemented flocele per sack plus own at 11:00 A.M Ran

CONDITIONS OF APPROVAL, IF ANY: