

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

3 - NMOC
1 - File

Form C-103
Supersedes Old
C-102 and C-103
Effective 4-65

JUN 27 4 20 PM '69

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Getty Oil Company	8. Farm or Lease Name E. D. McKinley
3. Address of Operator Box 249, Hobbs, New Mexico	9. Well No. 8
4. Location of Well UNIT LETTER H 2310 FEET FROM THE north LINE AND 430 FEET FROM THE east LINE, SECTION 30 TOWNSHIP 18 RANGE 38 N.M.P.M.	10. Field and Pool, or Without Undesignated
11. Elevation (Show whether BL, RL, GR, etc.) 3648.5 GR	12. Density Ion

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe in Reported or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 11" hole to 3843'. Set 8-5/8" 32# J-55 8R Casing at 3842'. Cemented with 1200 sacks Class "C" cement with 16% gel; 5# Gilsomite per sack; 1/4# floccle per sack and 33# salt per sack and 200 sacks Class "C" with 2% CaCl₂. Circulated an estimated 150 sacks cement. WOC 24 hours. Tested 8-5/8" casing at 1000# for 30 minutes, no drop in pressure.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY:

SIGNED C. L. Wade TITLE Area Supt. DATE June 19, 1969

APPROVED BY [Signature] TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: