

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions  
reverse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR HUMBLE OIL & REFINING COMPANY	8. FARM OR LEASE NAME BOWERS A FEDERAL
3. ADDRESS OF OPERATOR P.O. Box 1600, MIDLAND, TEXAS 79701	9. WELL NO. 31
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FROM N/L AND 660 FWL SEC 29	10. FIELD AND POOL, OR WILDCAT HOBBS-BLINEBRY
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 29, T-18-S, R-38-E
	12. COUNTY OR PARISH LEA
	13. STATE N. MEXICO

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRU BABER 12-16-71. PULLED TBG & PKR. PERF. BLINEBRY ZONE BY  
DRESSER @ 5856-5843' W/14 SHOTS AT 5807-5794, 14 SHOTS W/1-TSPF,  
RAN RET. B.P. & PKR. IN HOLE, SET BP AT 5945' & PKR AT 5750, 12-21-71.  
ACID PERFS W/5000 GAL 15% NE ACID, MAX PRESS 2450#, AVG  
PRESS 2300#, AIR 3.8 BPM. INSTANT SHUT-IN PRESS 1550#, AFTER  
5 MIN. 1100#. PULLED PKR. & B.P., 12-22-71. RAN BLINEBRY TBG.  
STRING. SET ANCHOR AT 5730, RAN PUMP & RODS AND TESTED 12-23-71.  
OIL IN HR PUMP TEST REC. 38 BO, 33 BLW. FRR 12-24-71.  
FRW 1-2-72

## 18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

UNIT HEAD

DATE

1-25-72

(This space for Federal or State official use)

APPROVED BY

TITLE

ACCEPTED FOR RECORD

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO