

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

5 - OCC
1 - Div. Prod. Mgr.
1 - Dist. Prod. Mgr.
1 - File

Form C-101
Revised 1-1-65

5A. Indicate Type of Lease
STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work		7. Unit Agreement Name	
b. Type of Well DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> SINGLE ZONE <input checked="" type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>		8. Farm or Lease Name H. D. McKinley	
2. Name of Operator Getty Oil Company		9. Well No. 10	
3. Address of Operator Box 249, Hobbs, New Mexico		10. Field and Pool, or Wildcat Hobbs Blinbry	
4. Location of Well UNIT LETTER B LOCATED 405 FEET FROM THE North LINE 2272 East 30 18 38 AND FEET FROM THE LINE OF SEC. TWP. RGE. NMPM		12. County Lea	
21. Elevations (Show whether DF, RT, etc.) 3657 GL.		19. Proposed Depth 6050	
21A. Kind & Status Plug. Bond Blanket 11-30-37		19A. Formation Blinbry	
21B. Drilling Contractor Pending		20. Rotary or C.T. Rotary	
22. Approx. Date Work will start When permit approved		23. St. Paul Indemnity	

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17-1/2"	13-3/8"	48	360	340	Surface
11"	8-5/8"	24 & 32	3850	1170*	Surface
7-7/8"	5-1/2"	15.5	6050	615*	3300'

* Actual volume to be determined by fluid check.

It is proposed to drill a 17-1/2" hole to 360' where the 13-3/8" surface casing will be set and cemented to the surface with 140 sx. Class C w/4% gel and 2% calcium chloride per sack followed with 200 sx Class C with 2% Cacl₂ per sack. Then an 11" hole will be drilled to 3850' where the 8-5/8" casing will be set. The 8-5/8" casing will be cemented to the surface. Then a 7-7/8" hole is to be drilled to 6050' where open hole logs will be run (Bershold compensated sonic - Gamma Ray, Dual Induction Laterolog, Microlog). The 5-1/2" casing to be set at 6050', cemented with 340 sx. Class C with 4% gel and 1/4% sx Cello-flake followed with 275 sx. Class C. Perforations in Blinbry zone to be selected after logging.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM; IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed BY

Signed **C. L. WADE**

Title **Area Superintendent**

Date **August 26, 1969**

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: