	· 	Form C-103
NO. OF COPIES RECEIVED	2	Supersedes Old
DISTRIBUTION	NEW HENIOD OH, CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	Firequive 1-1-62
FILE		5a. Indicate Type of Lease
U.S.G.S.		State X Fee
LAND OFFICE		5. State Oil & Gas Leage No.
OPERATOR		NM A-2747
(CO NOT USE THIS	SUNDRY NOTICES AND REPORTS ON WELLS S FORM FOR PROPERSALS TO LITEL OR TO DEEPEN OR PLUG SACK TO A DIFFERENT RESERVOIR. USE "MAPPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1.		7. Unit Agreement Name
Weight X	GAS OTHER.	
2. Stanle of Operator.	Marathon Oil Company	State Section 32
3. Address of Operator		9. Well No.
	P.O. Box 220, Hobbs, New Mexico 88240	9
4. Location of Well		10. Field and Fool, or Wildout
.1	2130 FEET FROM THE South LINE AND 1980 FEET FROM	Undesignated
UNIT LETTER	PEEC PROM THE	
East	LINE, SECTION 32 TOWNSHIP 18S RANGE 38E NMPM.	
THE	CIAE, SECTION TOTAL AND	
THITTITIT	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	KDB 3648'	Lea
16.	Check Appropriate Box To Indicate Nature of Notice, Report or Oth	er Data
NC	OTICE OF INTENTION TO: SUBSEQUENT	
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORAFILY ABANDON	COMMENCE DRILLING OPNS. X	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	
POLE OR PETER CADING	OTHER Cement surface of	asing
OTHER		
17. Describe Proposed of work) SEE RULE 11	or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any proposed
,		e dagli de delete en gelle delete de le servicio del
多种种类型 医甲基氏试验	क्षान्त्रकार कर के हिन्दे के अने अने अने अने अने अने अने अने अने अन	
	Spudded 17-1/2" hole November 1, 1969. and drilled to 37	76'. Ran

Spudded 17-1/2" hole November 1, 1969. and drilled to 376'. Rar 12 jts. 13-3/8" casing, 48#, H-40, overall length 357.00', effective length 352.80', and set from 11.20' below KDB to 364.00'. Bottom 3 jts. Baker locked and bottom 3 jts. centralized. Cemented with 160 sacks Class "C" 8% Gel, 2% CaCl₂. Cement circulated to surface. W.O.C. for 18 hrs., tested csg. with 1200 psi for 30 min. Held O.K.

•		
13. I hereby certify that the information above is true and complete	e to the best of my knowledge and belief.	
SIGNED DATESTANCE	TITLE Act. Area Supt.	DATE 11-12-69
APPROVED BY A STATE OF THE STAT	TITLE 1881V, 309 10 17 17 19	DATE
CONDITIONS OF APPROVAL, IF ANY:		
	·	