

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-065710

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

PLAINS UNIT Federal

8. FARM OR LEASE NAME

9. WELL NO.

10

10. FIELD AND POOL, OR WILDCAT

Lusk Delaware

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

28-19-32 NMPM

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

SUMMARY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. NAME OF OPERATOR

2. NAME OF OPERATOR

3. NAME OF OPERATOR

4. NAME OF OPERATOR

5. NAME OF OPERATOR

6. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

7. LOCATION OF WELL

860 FSL x 1900 FWL Sec. 28 (Unit N, SE 1/4 SW 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3754' R.D.B.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☒
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐
☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Production has declined below the economic limit w/ no
workover possibilities. Proposal to P+A as follows:

Spot 25 Sx cement plug across perfs 4719-4830

Shoot & pull 4 1/2" Csg from free point (Est TCMT 3500')

Float cement plug in & out 4 1/2" Csg plug and
across Yates permeability - 2830 - 2970'

Spot 40 Sx (200') in & out 9 7/8" phol (7 7/8" @ 2550' - Circ)

Spot 10 Sx @ Surface & Direct P+A marker.

Make final Cleanup and restore to contour.

TD-4855'

PRD-4893'

PERFS 4719-4830'

4 1/2" Csg 4895' w/200 Sx (TCMT-3500' Est)

7 7/8" Csg 2550' - Circ

MADE UNUSABLE
BY THE U.S. GEOLOGICAL SURVEY
EFFECTIVE 2/27/71

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE AREA SUPERINTENDENT

DATE JAN 2 1971

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

O+A-USGS-W

1-ACJ

1-SUSP

1-RRV

1-Mod:1

*See Instructions on Reverse Side

APPROVED

JAN 27 1971

ARTHUR R. BROWN
DISTRICT ENGINEER

RECEIVED

FEB 21 1971

OIL CONSERVATION COMM.
HONOLULU, H.I.