

Petroleum Information.

COUNTY LEA FIELD Maljamar DATE NM
 OPR PHILLIPS PETROLEUM CO. API 30-025-23343
 NO 10 LEASE Philmex MAP
Sec 27, T17S, R33E COORD 10-1-24 NM
1981 FSL, 1976 FWL of Sec RE-SPD 8-30-82 RE-MP 9-4-82
8 mi W/Buckeye

8 5/8-360-275 sx
 4 1/2-4632-275 sx
 2 3/8-4585

WELL CLASS. INIT		DX FINDO		LSE CODE	
FORMATION	DATUM	FORMATION	DATUM	FORMATION	DATUM
ID	4632 (SADR)	PHD	4619		

IP (Grayburg-San Andres) Perfs 4261-4598 P 34 BOPD + 17
 BW. Pot based on 24 hr test. GOR 1429; gty 36.7

CONTR OPRSTLY 4169 GL sub-s

F.R.C. 10-2-82 OWWO
 PD 4619 WO
 (Orig. Comp. 1-4-70 thru (Grayburg-San Andres) Perfs 4261-4598, OTD 4632, OPB 4619)
 9-27-82 TD 4632; PBD 4619; Complete
 Perf (San Andres) 4580-88 w/2 SPF
 Acid (4261-4598) 2500 gals
 10-2-82 COMPLETION ISSUED

10-1-24 NM
 IC 30-025-70739-82

COUNTY LEA FIELD Maljamar STATE NM 30-025-23343
 MAP
 OPR PHILLIPS PET. CO.
10 Philmex
Sec 27, T-17-S, R-33-E
1981' FSL, 1976' FWL of Sec.
Spd 12-14-69
Cmp 1-4-70
 CLASS
 FORMATION DATUM FORMATION DATUM
 CSG & SX - TUBING
 8 5/8" at 360' w/275 SX
 4 1/2" at 4632' w/275 SX
 LOGS EL GR RA IND HC A
 IP (Crayburg-San Andres) Perfs 4261-4398' P 133 BOPD + 82 BW.
 Pot based on 24 hr test. COR 1167; Crw 35.3.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus PROP DEPTH 4600' TYPE
 DATE

F.R. 10-28-69
 PD 4600' (Crayburg-San Andres)
 Contractor - Cactus
 Drlg. 1520' redbed
 12-16-69 Coring @ 4272'
 12-22-69 Cored 4130-80', rec 50' dolo & anhy, no shows
 Cored 4180-4230', rec 50' dolo & anhy, no shows
 1-6-70 ID 4632'; PED 4619'; Swbg
 Cored 4230-80', rec 50' dolo & sd w/show in sd
 Cored 4280-4330', rec 50' dolo & sd w/show in sd
 Cored 4330-80', rec 50' dolo & sd w/show in sd
 Cored 4380-4430', rec 50' dolo & sd w/show in sd
 Cored 4430-80', rec 50' dolo & sd w/show in sd
 Cored 4480-4530', rec 50' dolo & sh, no shows

SEA

PHILLIPS PET. CO.

Miljamar

NM

Sec 27, T17S, R33E

10 Philmex

Page #2

1-6-70

Continued

Cored 4730-50', rec 50' dolo w/shows

Cored 4780-4830', rec 50' dolo w/good shows

Perf 4261-68', 4307-12', 4396-4401', 4588-98'

Acid (4588-98') 1000 gals

Swbd 6 BNC + 18 BOW + 20 BAW in 5 hrs (4588-98')

TD 4632'; PEO 4619'; Reeg load

Swbd 20 BW + 10 BO in 4 hrs (4588-98')

Acid (4588-98') 5000 gals

swbd 38 BNC + 72 B salt w/c + 20 BO in 10 hrs

(4588-98')

Acid (4261-4401') 700 gals

Swbd dry (4261-4401')

Prac (4261-4598') 32,550 gals oil + 26,000# sd

1-20-70

1-26-70

TD 4632'; PEO 4619'; Reeg load

TD 4632'; PEO 4619'; COMPLETE

Log TOP: Anhydrite 2400', Yates 2801',
Queen 3764', Grayburg 4128', San Andres
4518'

1-29-70

COMPLETION REPORT