and provide the second second

THERE RELEASED STREETS AND DEPENDENCES 1. For the second seco second sec

131 131 y Contractor Carlo Carlos A Contractor Anna Anna Anna Anna Anna My the state of prove the state of 19 . 1900 - 15 a transformation of the second s

na dhuaite an an an an

Constant of Price Andrews Repairing Mathematica

10 ET 1 (1) A start of the start of (1) A strategies of provide the strategies of intermediate

and the second MENDMENT + / ADDITIONAL CEMENT PLUGS TO BE PLACED AS TOLICUS:

Surph N. 1974.

1.1 3

- 1. 25 sack cement plug in interval 3200 to 3300 feet. If pipe is not pulled below 3300 feet, this plug to be inside 52° casing. If casing is shot near this interval but not pulled, this cement plug should be below the shot point.
- 2. 25 sack cement plug in interval 1600 to 1700 feet.
- 3. Hole to be mudded between plugs with gel mud mixed with minimum of 2500 pounds gel per 100 barrels of water.

te a company de la company de la company La company de la company de	e se en el tr	Approved	1971	
a second on the density of the second sec		MAP 2 2 1974 APRIL		
n Alfred M Manifest - Marine Line	94	ANTINAR & ENCINA MICTRICT ENCINES		
		1 A. 4 (3.8		