

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER: Dry hole		7. Unit Agreement Name
2. Name of Operator Hanson Oil Company		8. Term of Lease Name Viersen
3. Address of Operator P. O. Box 1515, Roswell, New Mexico 88201		9. Well No. 1
4. Location of Well UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 30 TOWNSHIP 18-S RANGE 39-E NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3617' KB		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-11-70 Verbal request was made this date, and approved by Mr. Joe Ramey of the NMOC, Hobbs, to plug and abandon the captioned well in the following manner:

Set a 25 sx. cement plug at T. D. 7512'.
Set a 25 sx. cement plug at the Top of the Glorietta Fm.
Set a 25 sx. cement plug at the Top of the San Andres Fm.
Set a 25 sx. cement plug in-and-out of the 8-5/8" casing at 2923'.
Set a 25 sx. cement plug in-and-out of the 8-5/8" casing where shot off and pulled.
Set a 25 sx. cement plug in-and-out of 12-3/4" casing at 352'.
Set a 10 sx. cement plug at the surface and erect a regulation dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Harry T. Schum* TITLE Exec. Vice President DATE 2-11-70
APPROVED BY *[Signature]* TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: