

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No
E-6002

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Forest Oil Corporation	8. Farm or Lease Name B-Lee State
3. Address of Operator P. O. Box 4106, Odessa, Texas 79760	9. Well No. 7
4. Location of Well UNIT LETTER <u>E</u> , <u>2119</u> FEET FROM THE <u>North</u> LINE AND <u>918</u> FEET FROM THE <u>West</u> LINE, SECTION <u>7</u> TOWNSHIP <u>18-S</u> RANGE <u>35-E</u> NMPM.	10. Field and Pool, or Wildcat Vacuum
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Spudded at 1:00 P.M. 2/24/70 and drilled to 1,650'.
- Ran, set, and cemented 1,635' of 8-5/8" N-80 and J-55, 24#/ft. and 36#/ft. casing with insert float valve 1 jt. above guide shoe at 1,649' with 350 sx. Howco Lite Wate plug 200 sx. Incor neat cement. Circulated estimated 25 sx. W.O.C. 18 hrs. Tested 30 minutes with 800 psi - o.k.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. R. Clark TITLE Division Production Engineer DATE March 2, 1970

APPROVED BY Lester A. Clements TITLE Manager DATE MAR 4 1970

CONDITIONS OF APPROVAL, IF ANY: