DISTRIBUTION SANTA FE FILE	i e e e e e e e e e e e e e e e e e e e		Form C-103	,
			Supersedes Old C-102 and C-10	
I FILE	MEW MEXICO OIL CONS	SERVATION COMMISSION	Effective 1-1-6	-
	_			
U.S.G.S.			5a. Indicate Type	
LAND OFFICE			State X	Fee
OPERATOR			5. State Oil & Gas	Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (69 NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT _" FORM C-1011" FOR SUCH PROPOSALS.)				
I. OIL GAS WELL WELL	OTHER-		7. Unit Agreement	Name
2. Name of Operator Phillips Petroleum Company 3. Address of Operator			8, Farm or Lease Name	
			Philmex 9. Well No.	
Room B-2, Phillips B	31dg., Odessa, Texas 79760		12	
1 ., =	660 NET FHOM THE NORth	660	Undesignate	d - Grayburg
	TION 35 TOWN SEAD 17-			
	15. Lievanca (Show whether Later	DF, RT, GR, etc.)	12. County	
Check	k Appropriate Box To Indicate N	Nature of Notice Report or C	Lea Other Data	
	INTENTION TO:		NT REPORT OF:	
PERFORM REMEDIAL WORK	PLIG AND ABANE IN		ALTERIN	IG CASING
TEMPORAPILY ABANDON		CARMENCE DATE, THE OPEN. CARING TEST AND DEMENT DOS.	PLUG AN	D ABANDONMENT
PULL OR ALTER CASING	CHONSE = ANS	CAGING TEST AND SEMENT SQB		<u> </u>
	;	OTHER		
OTHER				
Control Ded 11de - Com-				
(160 jts, 4789 ft) at followed by 150 sx C. Max press 2000#. Csg rig. Ran temperature	any drilled 7-7/8" hele to 0' and reached TD of 4790 cleg. Cond hele. Set 4-1 t 4789'. Dewell cemented lass H neat cement. Plug retated. Job completed le survey, TOC outside casir 1/2 hour, ekey. Prep to	' on 11-12-70. Schlumb 1/2" OD, 11.6#, N-80, A on 11-13-70 with 150 a to 4787' w/10% acetic 12:30 P.M., 11-13-70. ing at 2750'. WOC. ins	erger ran BHC cond, casing ox Class H 40% acid and 64 B	-Sonic, DD
GR_Caliper and Later (160 jts, 4789 ft) at followed by 150 sx C. Max press 2000#. Csg rig. Ran temperature casing with 2000# for	oleg. Cond hole. Set 4-10 cleg. Cond hole. Set 4-10 t 4789'. Dewell cemented lass H neat cement. Plug retated. Job completed le survey, TOC outside cast r 1/2 hour, ekey. Prep to	'en 11-12-70. Schlumb 1/2" OD, 11.6#, N-80, A en 11-13-70 with 150 s to 4787' w/10% acetic 12:30 P.M., 11-13-70. ing at 2750'. WOC, inso complete.	erger ran BHC cond, casing ox Class H 40% acid and 64 B	-Sonic, DD
GR-Caliper and Later (150 jts, 4789 ft) at followed by 150 sx C. Max press 2000#. Csg rig. Ran temperature casing with 2000# for	oleg. Cond hole. Set 4-1 t 4789'. Dewell cemented lass H neat cement. Plug retated. Job completed le survey, TOC outside casi r 1/2 hour, okey. Prep to	on 11-12-70. Schlumbl/2" OD, 11.6#, N-80, A en 11-13-70 with 150 at to 4787' w/10% acetic 12:30 P.M., 11-13-70. ing at 2750'. WOC, inso complete.	erger ran BHC cond, casing x Class H 40% acid and 64 B Released Cact talled tiedown	-Sonic, DD W. us (on 11-16- ns,/tested
GR-Caliper and Later (150 jts, 4789 ft) at followed by 150 sx C. Max press 2000#. Csg rig. Ran temperature casing with 2000# for	oleg. Cond hole. Set 4-1 t 4789'. Dewell cemented lass H neat cement. Plug retated. Job completed le survey, TOC outside casi r 1/2 hour, okey. Prep to	'en 11-12-70. Schlumb 1/2" OD, 11.6#, N-80, A en 11-13-70 with 150 s to 4787' w/10% acetic 12:30 P.M., 11-13-70. ing at 2750'. WOC, inso complete.	erger ran BHC cond, casing x Class H 40% acid and 64 B Released Cact talled tiedown	-Sonic, DD W. us (on 11-16- ns,/tested
GR_Caliper and Later (160 jts, 4789 ft) at followed by 150 sx C. Max press 2000#. Csg rig. Ran temperature casing with 2000# for	oleg. Cond hole. Set 4-1 t 4789'. Dewell cemented lass H neat cement. Plug retated. Job completed le survey, TOC outside casi r 1/2 hour, okey. Prep to	on 11-12-70. Schlumbl/2" OD, 11.6#, N-80, A en 11-13-70 with 150 at to 4787' w/10% acetic 12:30 P.M., 11-13-70. ing at 2750'. WOC, inso complete.	erger ran BHC cond, casing x Class H 40% acid and 64 B Released Cact talled tiedown	-Sonic, DD W. us (on 11-16- ns,/tested
GR-Caliper and Later (160 jts, 4789 ft) at followed by 150 sx C. Max press 2000#. Csg rig. Ran temperature casing with 2000# for	oleg. Cond hole. Set 4-1 t 4789'. Dewell cemented lass H neat cement. Plug retated. Job completed le survey, TOC outside casi r 1/2 hour, okey. Prep to	on 11-12-70. Schlumbl/2" OD, 11.6#, N-80, A en 11-13-70 with 150 at to 4787' w/10% acetic 12:30 P.M., 11-13-70. ing at 2750'. WOC, inso complete.	erger ran BHC cond, casing x Class H 40% acid and 64 B Released Cact talled tiedown	-Sonic, DD W. us (on 11-16- ns,/tested

RECEIVED

MOY 2: 1979
OIL CONSERVATION COMM.
HODDS N. D.