

COUNTY LEA FIELD Lusk STATE NM 30-025-23727

OPR TEXACO INC. MAP

1x New Mexico "DH" State

Sec 32, T-19-S, R-32-E CO-ORD

380' FNL, 330' FEL of Sec

Spd 3-13-71 CLASS EL 3558' 2

Cmp 5-20-71

CSG & SX - TUBING

10 3/4" at 900' w/680 sx

7 5/8" at 2800' w/350 sx

5 1/2" at 3539' w/150 sx

4" lnr 3324-5049' w/154 sx.

LOGS EL GR RA IND HC A

TD 5050'; PBD 4978'

IP (Delaware Sand) Perfs 4760-4808' P 8 BOPD + 18 BW. Pot based

on 24 hr test. GOR TSTM; Grav 39.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Logging Service, Inc.

CONT. Cactus PROP DEPTH 5050' TYPE RT

DATE

F.R. 3-16-71; Opr's Elev. 3551' CL

PD 5050' RT (Delaware)

Contractor - Cactus

(Replacement for well #1, Junked & Abandoned

3-15-71 TD 900'; Prep run casing

3-22-71 Drlg. 3295'

3-29-71 TD 3490' 1m; Reaming

Lost Circ @ 3476'

Sqzd (OH 2800-3450') w/2600 sx

4-5-71 TD 3532'; Fshg

4-12-71 TD 3532'; Prep run casing

Recovered Fish

4-19-71 TD 3532'; Fshg

4-26-71 Drlg. 4425' 1m & sh

LEA
TEXACO INC.

Lusk NM Sec 32, T19S, R32E
1x New Mexico "DH" State Page #2

5-3-71 TD 5050'; WOC
5-10-71 TD 5050'; PBD 4978'; Prep Frac
Perf 4760-66', 4774-80', 4804-08',
4812-16' w/1 SPF
Acid (4760-4816') 1000 gals
5-17-71 TD 5050'; PBD 4978'; Ppg load
Frac (4760-4816') 6000 gals kerosene +
9500# sd
5-24-71 Ppd 6 BLO + 23 BIW + 17 LEW in 24 hrs
TD 5050'; PBD 4978'; WO potential
Ppd 8 BO + 18 BW in 24 hrs; GOR TSTM
6-7-71 TD 5050'; PBD 4978'; COMPLETE
LOG TOPS: Anhydrite 845', Gates 2600', Seven
Rivers 2740', Delaware sand 4750'
6-10-71 COMPLETION REPORTED