

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>Gulf Oil Corporation</b>	8. Farm or Lease Name <b>Dan W. Hardin</b>
3. Address of Operator <b>Box 670, Hobbs, New Mexico 88240</b>	9. Well No. <b>9</b>
4. Location of Well UNIT LETTER <b>0</b> <b>580</b> FEET FROM THE <b>South</b> LINE AND <b>2310</b> FEET FROM THE <b>East</b> LINE, SECTION <b>18</b> TOWNSHIP <b>18-S</b> RANGE <b>38-E</b> NMPM.	10. Field and Pool, or Wildcat <b>Hobbs</b>
15. Elevation (Show whether DF, RT, GR, etc.)	12. County <b>Lea</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moran Drilling Company spudded 11" surface hole at 9:30 AM, May 19, 1971. Drilled to 298'. Ran 9 joints, 282' of 8-5/8" OD 21# K-55 ST&C casing set and cemented at 295' with 275 sacks of Class C cement containing 2% Ca Cl2. Cement circulated.

WOC & NU 22 hours. Tested casing with 800#, 30 minutes, OK. Started drilling 7-7/8" hole at 298' at 7:00 PM, May 20, 1971.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY  
**C. F. KALTEYER**

SIGNED \_\_\_\_\_ TITLE **Area Petroleum Engineer** DATE **May 21, 1971**

APPROVED BY \_\_\_\_\_ TITLE **SUPERVISOR DISTRICT** DATE **MAY 24 1971**

CONDITIONS OF APPROVAL, IF ANY

RECEIVED

MAY 21 1971

OIL CONSERVATION COMM.  
HOBBS, N. M.