

COUNTY LEA FIELD Hobbs STATE NM 30-025-23919
 OPR HUMBLE OIL & REFG. CO. MAP
 35 Bowers "A" Fed Com CO-ORD
 Sec 29, T-18-S, R-38-E
 990' FNL, 330' FWL of Sec
 Spd 11-9-71
 Cmp 12-1-71
 CSG & SX - TUBING
 8 5/8" at 310' w/150 sx
 5 1/2" at 3905' w/300 sx.
 LOGS EL GR RA IND HC A
 TD 4331'; PBD 4250'
 IP (Grayburg-San Andres) OH 3905-4250' F 122 BOPD + 65 BW. Pot
 based on 24 hr test thru 25/64" chk. GOR 1393; Grav 32.5; CP Pkr;
 TP 175#.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.
 CONT Leatherwood PROP DEPTH 4250' TYPE RT
 DATE

11-15-71 F.R. 10-26-71; Opr's Elev. 3661' DF
 11-22-71 PD 4250' RT (Grayburg-San Andres)
 11-29-71 Contractor - Leatherwood
 12-6-71 Drlg. 3485' lm
 Drlg. 4316' lm & dolo
 TD 4331'; PBD 4288'; WOC
 TD 4331'; PBD 4288'; Prep PB
 Acid (4260-88') 500 gals
 Swbd 4 BO + 34 BW in 10 hrs (3905-4288')
 12-13-71 TD 4331'; PBD 4250'; WO Potential
 PB to 4250'
 Flwd 122 BO + 65 BW in 24 hrs thru 25/64" chk.
 TP 200#
 12-20-71 TD 4331'; PBD 4250'; COMPLETE
 LOG TOPS: Grayburg 3988', San Andres 4092'
 12-23-71 COMPLETION REPORTED