

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL ☒ GAS WELL ☒ OTHER	5. LEASE DESIGNATION AND SERIAL NO. NM 063530
2. NAME OF OPERATOR Sun Oil Company (Delaware)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 1861, Midland, Texas 79701	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FWL & 1980' FSL of Section 15	8. FARM OR LEASE NAME Shearn Federal Com.
14. PERMIT NO. Approved 11-30-71	9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RL, GR, etc.) Ground 3621.3 KB 3642	10. FIELD AND POOL, OR WILDCAT Wildcat
	11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec. 15-19S-32E
	12. COUNTY OR PARISH Lea
	13. STATE New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) Plug Back & Test ☒	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Drilled 6 1/2" hole to TD 14,330' on 3-10-72
Top Devonian 13,964'

Tentative plans are to plug back to approximately 13,000' and test a Morrow porosity zone 12,231-239'.

Run open ended drill pipe to TD and spot 100 sack plug of Class H cement 14,330-13,875'
Spot 80 sack plug 13,400-13,000' (7 5/8" Liner set 13,342')

Perforate Morrow 12,231-239. Run tubing and packer and test. Size and type of treatment to be contingent upon test results.

NOTE: Discussed plug back procedure with Mr. Arthur Brown, by telephone 3-10-72.

18. I hereby certify that the foregoing is true and correct

SIGNED W. E. Westbrook, Jr.TITLE District Drlg. EngineerDATE 3-14-72

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

APPROVED
MAR 20 1972ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

RECEIVED
JUN 10 1964
U.S. DEPT. OF THE INTERIOR