

Application for SWD

Philmex No. 14 M-28-17-33

Page 2

<u>Well Name & Location</u>	<u>T.D.</u>	<u>Csg Size & Setting Depth</u>	<u>Sacks of Cement Used</u>	<u>Estimated TOC</u>	<u>Producing Interval</u>
Cities Service Oil Co.--SEMGSAU 9-02 A-32-17-33	4314'	8-5/8" @ 1257' 5-1/2" @ 4050'	50 sxs 100 sxs	1021' 3358'	4050'-4314'
Cities Service Oil Co.--SEMGSAU 9-04 A-32-17-33	4271'	8" @ 1300' 7" @ 3943'	50 sxs 100 sxs	1064' 3255'	3943'-4266'
Ed Spears--U.S. Minerals Fed. No. 1 D-33-17-33	4303'	12-1/2" @ 235' 10" @ 705' 8" @ 930' 7" @ 1427' 5-1/2" @ 4278'	100 sxs	3586'	4278'-4303'
Ed Spears--U.S. Minerals Fed. No. 2 D-33-17-33	4302'	8-5/8" @ 1306' 7" @ 4104'	50 sxs 100 sxs	1070' 3416'	4104'-4302'
Ed Spears--Wyatt Phillips Fed. No. 3 E-33-17-33	4300'	7" @ 1330' 5-1/2" @ 3719'	50 sxs 50 sxs	986' 3373'	3719'-4300'
H. R. Denius--Wyatt Phillips Fed. No. 5 C-33-17-33	4305'	8" @ 1200' 7" @ 1220' 4" @ 4305'	100 sxs 50 sxs 100 sxs	814' 876' 3827'	4258'-4305'
Ed Spears--Wyatt Phillips Fed. No. 12 C-33-17-33	4310'	8-5/8" @ 224' 5-1/2" @ 4200'	50 sxs 600 sxs	Surface Surface	4200'-4310'
Ed Spears--Wyatt Phillips Fed. No. 1 C-33-17-33	4506'	10-1/2" @ 315' 4-1/2" @ 4499'	250 sxs 1200 sxs	Surface Surface	4375'-4377'
James P. Dunigan--Cockburn No. 1 D-33-17-33	8940'	13-3/8" @ 308' 8-5/8" @ 4557'	340 sxs 1950 sxs	Surface 1400'	Dry Hole P&A