

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.

NM 4160

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amini Oil Company	8. Farm or Lease Name Shell "A" State
3. Address of Operator 405 Wall Towers East - Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>L</u> 1980 FEET FROM THE <u>South</u> LINE AND <u>860</u> FEET FROM THE <u>West</u> LINE, SECTION <u>1</u> TOWNSHIP <u>17-S</u> RANGE <u>34-E</u> NMPM.	10. Field and Pool, or Wildcat N. Vacuum Abo
15. Elevation (Show whether DF, RT, GR, etc.) 4041.9 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 12-29-72 Drilled 7-7/8" hole to TD @ 8795'. Ran 276 jts. 4 1/2" csg. (11.60# N-80 & J-55 8rd lt & c) to 8795' & cemented w/650 sx Halliburton lite & w/300 sx class C w/8# salt per sk. & 3/4 of 1% CFR per sk. Plugged down 6:30 PM.
- 12-30-72 Temp. Survey. Top of cement 3800'; W.O.C. 24 hrs - tested w/1000 psi for 30 mins. - held ok.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Harin Godwin</u>	TITLE <u>Agent</u>	DATE <u>Jan. 8, 1973</u>
APPROVED BY <u>Joe D. Ramey</u>	TITLE <u>Dist. I Supv.</u>	DATE <u>Jan 10 1973</u>
CONDITIONS OF APPROVAL, IF ANY:		