

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.
B-1080-1

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <u>Water Injection</u>	7. Unit Agreement Name <u>Vacuum Grayburg San Andres Unit</u>
2. Name of Operator <u>TEXACO Inc.</u>	8. Former Lease Name <u>Vacuum Grayburg San Andres Unit</u>
3. Address of Operator <u>P. O. Box 728, Hobbs, New Mexico 88240</u>	9. Well No. <u>33</u>
4. Location of Well: UNIT LETTER <u>E</u> <u>2630</u> FEET FROM THE <u>North</u> LINE AND <u>1310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>1</u> TOWNSHIP <u>18-S</u> RANGE <u>34-E</u> NMPM.	10. Field and Pool or Wildcat <u>Vacuum Grayburg San Andres</u>
15. Elevation (Show whether DF, RT, GR, etc.) <u>3993' (GR)</u>	12. County <u>Lea</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER Repair Inlater Flow ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. RUGGED UP. PULL TUBING AND PACKER.
2. SET RBP @ 4000' AND SPOT 2 SX SAND ON PLUG.
3. PERFORATE 4 1/2" CASING W/2-JS @ 1480'.
4. SET CEMENT RETAINER @ 1397'. CEMENT SQUEEZED PERFS @ 1480' W/550 SX CLASS H CEMENT CONTAINING 2% CACL. CEMENT DID NOT CIRCULATE. WOC. DOC. TESTED 4 1/2" CASING TO 600# FOR 30 MINUTES, 3:00-3:30 PM, 4-2-84. TESTED OK.
5. PERFORATE 4 1/2" CSG W/2-JSPF @ 385'.
6. CEMENTED W/200 SX. CLASS H CEMENT CONTAINING 2% CACL. CEMENT CIRCULATED. WOC. DOC.
7. TESTED CSG TO 600# FOR 30 MINUTES. TESTED OK.
8. RUN INJECTION TUBING AND PACKER. LOAD ANNULUS W/INHIBITED WATER. RETURN WELL TO WATER INJECTION.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Asst Dist Mgr

DATE 4-12-84

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____

TITLE _____

DATE APR 13 1984

CONDITIONS OF APPROVAL, IF ANY: